



	<a href="#">AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HFW1500TL-A-0360B-S2 - 5 Mpx 3.6 mm DAHUA</a>	<a href="#">AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HFW1500TH-I8-0360B-S2 5 Mpx 3.6 mm DAHUA</a>
		
	84.77 EUR 84.77 EUR	81.16 EUR 81.16 EUR
Standard	AHD, HD-CVI, HD-TVI, CVBS	AHD, HD-CVI, HD-TVI, CVBS
Sensor	1/2.7 " Progressive Scan CMOS	1/2.7 " Progressive Scan CMOS
Matrix size	5 Mpx	5 Mpx
Resolution	2880 x 1620 - 5 Mpx HD-CVI only , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p HD-CVI only 960 x 576 - 960H	2880 x 1620 - 5 Mpx - HD-CVI only : Aspect Ratio 16 : 9 , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p - HD-CVI only 960 x 576 - 960H, PAL
Lens	3.6 mm	3.6 mm
View angle	<ul style="list-style-type: none"> <li>• 92 ° (manufacturer data)</li> <li>• 90 ° (our tests result)</li> </ul>	<ul style="list-style-type: none"> <li>• 92 ° (manufacturer data)</li> <li>• 88 ° (our tests result)</li> </ul>
Range of IR illumination	80 m	80 m
IR illuminator power adjustment	Automatic	Automatic
Video output	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Audio	Microphone built-in, HD-CVI only	—
OSD menu	✓	OSD menu available via DAHUA recorder
Main features	<ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• 2D-DNR - Digital Noise Reduction</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Day/night mode</li> <li>• ICR - Movable InfraRed filter</li> <li>• Auto White Balance</li> <li>• AGC - Automatic Gain Control</li> <li>• Sharpness - sharper image outlines</li> <li>• Privacy zones</li> <li>• Mirror - Mirror image</li> </ul>	<ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• 2D-DNR - Digital Noise Reduction</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Day/night mode</li> <li>• ICR - Movable InfraRed filter</li> <li>• Sharpness - sharper image outlines</li> <li>• AGC - Automatic Gain Control</li> <li>• Privacy zones</li> <li>• Mirror - Mirror image</li> <li>• Auto White Balance</li> </ul>
Power supply	12 V DC / 430 mA	12 V DC / 440 mA

Power consumption	≤ 5.2 W	≤ 5.2 W
Housing	Compact, Plastic + Metal	Compact, Plastic + Metal
Color	White + Black	White + Black
"Index of Protection"	IP67	IP67
Operation temp	-40 °C ... 60 °C	-40 °C ... 60 °C
Weight	0.28 kg	0.41 kg
Dimensions	199 x 80 x 76 mm	Ø 90 x 241 mm
Manufacturer / Brand	DAHUA	DAHUA
Guarantee	3 years	3 years