



	PROGRAMMER DT-PG1 VIDOS	POWER DISTRIBUTION UNIT ACAR-504/WF/RACK
		
	11538.46 HUF 11538.46 HUF	14515.38 HUF 14515.38 HUF
Rated voltage	...	230 V AC
Compatibility	U1014-2	...
Rated current	...	10 A (total)
Connectors type	SW+ / SW- socket	...
Response time	...	< 25 ns
Main features	<ul style="list-style-type: none"> • DIP SWITCH for configuration and addressing, • Programming key 	...
Nominal voltage of surge suppressor	...	250 V / 50 Hz
Power supply	1 x CR2032	...
Protection level of surge suppressor	...	≤ 1.3 kV (L/N)
Nominal stroke current	...	2.5 kA (L/N) - 8/20 μs
Maximum stroke current	...	6.5 kA (L/N) - 8/20 μs
Manufacturer / Brand	VIDOS	...
Leak current	...	< 0.5 mA
Number of outlets	...	5 grounded outlets 10A/250V
Switch	...	two-way, with light indication
Length of the cable	...	2.7 m
Housing	...	RACK 19", 1U, Plastic - non-flammable
Dimensions	64 x 46 x 18 mm	383 x 58 x 55 mm
Weight	0.02 kg	0.59 kg
Guarantee	3 years	2 years