



	ACCESS CONTROLLER WITH FACE RECOGNITION DS-K1T341AM-S - 720p Hikvision	ACCESS CONTROLLER WITH TEMPERATURE MEASUREMENT ASI7213X-T1 - 1080p DAHUA
		
	480.02 EUR 480.02 EUR	3515.51 EUR 3515.51 EUR
Sensor	CMOS	1/2.8 " CMOS
Optical zoom	...	—
Cards support	13.56 MHz S50	...
Matrix size	2 Mpx	2.1 Mpx 120 x 90 px
Memory	<ul style="list-style-type: none"> • Memory of 1500 face templates • Memory of 1500 RFID cards • Non-volatile log buffer of the last 150 000 events 	...
View angle	...	50 °
Resolution	1280 x 720 - 720p	1920 x 1080 - 1080p 120 x 90 px
IR illuminator	—	...
LED illuminator	—	...
Standard	TCP/IP	TCP/IP
Range of IR illumination	...	5 m
White light LED illuminator range	...	5 m
Temperature measurement	...	✓
Temperature measurement range	...	30 °C ... 50 °C
Accuracy of temperature measurement	...	± 0.1 °C
Face recognition distance	0.3 m ... 1.5 m	0.3 m ... 1.8 m (max 100 000 faces in the database)
RFID proximity reader built-in	...	13.56 MHz S50
Internal memory	...	Support storage of 300 000 records
Video output	—	—

RS-485 interface	✓	✓
RS-232 interface	...	✓
Wiegand interface	...	✓
USB	...	2 x USB 2.0
Memory card slot	—	—
Alarm inputs / outputs	—	2 / 2 - Relay outputs
Audio	Speaker built-in	Speaker built-in
Network interface	10/100/1000 Mbps (RJ-45)	• 1 x 10/100 Base-T (RJ-45) • 1 x 10/100/1000 Base-T (RJ-45)
Network protocols	TCP/IP, ISUP, ISAPI	IPv4, RTSP, RTP, TCP, UDP, P2P
WEB Server	Built-in	Built-in
ONVIF	—	✓
Default IP address	192.168.1.64	192.168.1.108
Default admin user / password	admin / - The administrator password should be set at the first start	admin / - The administrator password should be set at the first start
Web browser access ports	80	80, 37777
PC client access ports	port 8000	37777
SAP Code	302917454	...

Main features	<ul style="list-style-type: none"> • 4.3 " capacitive touch screen • Mechanical tamper protection • WDR - Wide Dynamic Range • AI detection : Face recognition • Configuration and management from the iVMS-4200 application • Port USB • Recording of information about Time&Attendance • Possibility to open the gate using a QR code • Door lock control output • Possibility to connect an exit button and a reed switch to control the door status 	<ul style="list-style-type: none"> • Temperature measurement • Built-in LCD display showing the image from the video camera and the result of temperature measurement - 7 " capacitive touch screen, 1024 x 600 px • Identification modes : PIN, Proximity identifier 13.56 MHz S50, Face recognition, Any combination of the above • Wiegand 34/26 • WDR - 120 dB - Wide Dynamic Range • LED indication • Buzzer for acoustic signaling of some system events • AGC - Automatic Gain Control • Sharpness - sharper image outlines • Day/Night mode (color/b&w/auto) • RESET button • AI detection : A solution dedicated to measuring temperature. The camera is able to detect increased object temperature
Power supply	12 V DC / 2 A (power adapter included)	12 V DC / 2 A (power adapter included)
Power consumption	≤ 24 W	≤ 24 W
Housing	Metal	Aluminum + Tempered glass
Color	Black / Silver	Black + Silver
"Index of Protection"	—	—
Operation temp	-30 °C ... 60 °C	<ul style="list-style-type: none"> • -10 °C ... 55 °C - without temperature measurement • 15 °C ... 32 °C - with temperature measurement
Weight	0.31 kg	2 kg
Dimensions	173 x 83 x 23 mm (without bracket)	313 x 130 x 59 mm
Montage hole diameter	...	37 mm
Supported languages	English, German, French, Polish, Czech, Hungarian, Bulgarian, Serbian, Slovenian, Albanian	English
Manufacturer / Brand	Hikvision	DAHUA
Guarantee	3 years	3 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00