




| | RFID PROXIMITY CARD ID-EM DAHUA | LABORATORY METER UT-801 UNI-T |
|---|---|--|
| |  |  |
| | 1.92 EUR 1.92 EUR | 104.10 EUR 104.10 EUR |
| Standard | Unique EM 125kHz | ... |
| Compatibility | EM4100/4102 | ... |
| Possibility of programming the serial number (ID) | — | ... |
| Ability to write to internal memory | — | ... |
| Serial Number overprint | ✓ | ... |
| DC voltage measurement | ... | <ul style="list-style-type: none"> • 200 mV ± (0.5% + 2) @ 0.1 mV, • 2 V ± (0.5% + 2) @ 1 mV, • 20 V ± (0.5% + 2) @ 10 mV, • 200 V ± (0.5% + 2) @ 100 mV, • 1000 V ± (0.8% + 3) @ 1 V |
| AC voltage measurement | ... | <ul style="list-style-type: none"> • 2 V ± (0.8% + 3) @ 1 mV, • 20 V ± (1.0% + 4) @ 10 mV, • 200 V ± (1.0% + 4) @ 100 mV, • 1000 V ± (1.0% + 4) @ 1 V |
| DC current measurement | ... | <ul style="list-style-type: none"> • 200 µA ± (0.8% + 2) @ 0.1 µA, • 2 mA ± (0.8% + 2) @ 0.001 mA, • 20 mA ± (0.8% + 2) @ 0.01 mA, • 200 mA ± (0.8% + 2) @ 0.1 mA, • 10 A ± (2.0% + 4) @ 0.01 A |
| AC current measurement | ... | <ul style="list-style-type: none"> • 2 mA ± (1.0% + 3) @ 0.001 mA, • 20 mA ± (1.0% + 3) @ 0.01 mA, • 200 mA ± (1.0% + 3) @ 0.1 mA, • 10 A ± (2.5% + 5) @ 0.01 A |

| | | |
|--------------------------------------|------------------|--|
| Resistance measurement | ... | <ul style="list-style-type: none"> • 200 Ω ± (0.8% + 3) @ 0.1 Ω, • 2 kΩ ± (0.8% + 3) @ 1 Ω, • 20 kΩ ± (0.8% + 3) @ 10 Ω, • 200 kΩ ± (0.8% + 3) @ 100 Ω, • 2 MΩ ± (0.8% + 3) @ 1 kΩ, • 20 MΩ ± (1.2% + 5) @ 10 kΩ |
| Capacitance measurement | ... | <ul style="list-style-type: none"> • 20 nF ± (4% + 3) @ 0.01 nF, • 2 μF ± (4% + 3) @ 0.001 μF, • 200 μF ± (5% + 5) @ 0.1 μF |
| Inductance measurement | ... | — |
| Frequency measurement | ... | <ul style="list-style-type: none"> • 2 kHz ± (1.5% + 5) @ 1 Hz, • 200 MHz ± (1.5% + 5) @ 100 Hz |
| Temperature measurement | ... | <ul style="list-style-type: none"> • -40 °C ... -20 °C ± (8% + 5) @ 1 °C, • -20 °C ... 0 °C ± (1.2% + 4) @ 1 °C, • 0 ... 100 °C ± (1.2% + 3) @ 1 °C, • 100 ... 1000 °C ± (2.5% + 2) @ 1 °C |
| Automatic change of measuring ranges | ... | — |
| hFE | ... | ✓ |
| Diode test | ... | ✓ |
| Sound signal of the continuity test | ... | ✓ |
| Checking TTL logic states | ... | — |
| RS-232 | ... | — |
| USB | ... | — |
| Main features | ... | <ul style="list-style-type: none"> • Large, readable LCD display with backlight • Hold - stopping the meter reading • Aesthetic and solid construction |
| Power supply | ... | <ul style="list-style-type: none"> • 6 x 1.5V, type R14/LR14 battery (not included), • 9 V DC / 200 mA (power adapter included) |
| Weight | 0.006 kg | 1.61 kg |
| Dimensions | 86 x 54 x 0.8 mm | 306 x 243 x 107 mm |

| | | |
|----------------------|---------|---------|
| Manufacturer / Brand | DAHUA | UNI-T |
| Guarantee | 3 years | 2 years |



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00