





|  |  |   |  |   |
|--|--|---|--|---|
|  | <a href="#">SMART SWITCH WITH TEMPERATURE AND HUMIDITY MEASUREMENT ATLO-TS2-TUYA Wi-Fi, Tuya Smart</a>                       | <a href="#">IP CAMERA IPC2125LE-ADF28KM-G-BLACK - 5 Mpx 2.8 mm UNIVIEW</a>  | <a href="#">WIRELESS GAS DETECTOR ATLO-MD1-TUYA Wi-Fi, Tuya Smart</a>  | <a href="#">ELECTRICAL INSTALLATION CONNECTION KZ-37-UV</a>                         |
|  |   |                                  |    |  |
|  | 25.62 AUD<br>25.62 AUD   | 298.76 AUD<br>298.76 AUD  | 23.17 AUD<br>23.17 AUD   | 0.82 AUD<br>0.82 AUD  |
| Inner diameter                           | ...  | ...   | ...  | Ø 37 mm   |
| Standard                                 | ...  | TCP/IP  | ...  | ...   |
| Support                                  | ...  | ...   | Tuya Smart   | ...   |
| Application                              | <ul style="list-style-type: none"> <li>• temperature and humidity measurement</li> <li>• switching devices on/off</li> </ul> | ...   | ...  | ...   |
| Sensor                                   | ...  | 1/2.7 " Progressive Scan CMOS   | ...  | ...   |
| Matrix size                              | ...  | 5 Mpx   | ...  | ...   |
| Detection                                | ...  | ...   | <ul style="list-style-type: none"> <li>• Flammable gases,</li> <li>• Natural gas (methane),</li> <li>• LPG (propane-butane) gas</li> </ul> | ...   |
| Pipe mounting method                     | ...  | ...   | ...  | Pressing  |
| Temperature measurement                  | -20 °C ... 80 °C ± 0.5 °C  | ...   | ...  | ...   |
| Alarm signaling                          | ...  | ...   | <ul style="list-style-type: none"> <li>• Buzzer</li> <li>• LED indicator</li> <li>• Signal to the Tuya Smart mobile application</li> </ul> | ...   |
| Gas concentration to trigger alarm       | ...  | ...   | 6% ±3% Lower Explosive Limit (LEL)   | ...   |
| Prealarm feature                         | ...  | ...   | —  | ...   |
| Measurement of humidity                  | 5 % ... 90 % ± 3 %   | ...   | ...  | ...   |
| Autodiagnostics                          | ...  | ...   | —  | ...   |
| Maximal total load                       | 3000 W   | ...   | ...  | ...   |
| Resolution                               | ...  | 2880 x 1620 - 5 Mpx ,<br>2560 x 1440 - 3.7 Mpx ,<br>2304 x 1296 - 3 Mpx ,<br>1920 x 1080 - 1080p                  | ...  | ...   |
| Total maximal current                    | 16 A   | ...   | ...  | ...   |
| Lens                                     | ...  | 2.8 mm  | ...  | ...   |
| Number of inputs                         | 1  | ...   | ...  | ...   |
| Frequency band                           | ...  | ...   | 2.4 GHz WiFi IEEE 802.11 b/g/n   | ...   |
| Number of outputs                        | 1  | ...   | ...  | ...   |
| Radio communication range (at open area) | ...  | ...   | The range limited only by the availability of the Wi-Fi network  | ...   |
| Connector type                           | screw terminals  | ...   | ...  | ...   |
| View angle                               | ...  | <ul style="list-style-type: none"> <li>• 113 ° (manufacturer data)</li> <li>• 104 ° (our tests result)</li> </ul> | ...  | ...   |
| Range of IR illumination                 | ...  | 50 m  | ...  | ...   |
| S/N ratio                                | ...  | > 52 dB   | ...  | ...   |
| Wireless                                 | <ul style="list-style-type: none"> <li>• Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n</li> <li>• Bluetooth</li> </ul>                  | ...   | ...  | ...   |
| RS-485 interface                         | ...  | —   | ...  | ...   |

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

|                               |  |   |   |   |
|-------------------------------|--|---|---|---|
| Memory card slot              | ...  | Micro SD memory cards up to 256GB support (possible local recording)  | ...   | ...   |
| Image compression method      | ...  | Ultra 265 / H.265 / H.264 / MJPEG   | ...   | ...   |
| Alarm inputs / outputs        | ...  | —   | ...   | ...   |
| Audio                         | ...  | <ul style="list-style-type: none"> <li>• Microphone built-in</li> <li>• Audio transmission via network</li> <li>• Audio detection</li> </ul>  | ...   | ...   |
| Main stream frame rate        | ...  | 25 fps @ 5 Mpx  | ...   | ...   |
| Network interface             | ...  | 10/100 Base-T (RJ-45)   | ...   | ...   |
| WEB Server                    | ...  | Built-in  | ...   | ...   |
| Max. number of on-line users  | ...  | 32  | ...   | ...   |
| ONVIF                         | ...  | ✓   | ...   | ...   |
| Mobile phones support         | <ul style="list-style-type: none"> <li>• The <a href="#">Tuya Smart</a> free application on Android</li> <li>• The <a href="#">Tuya Smart</a> free application on iOS</li> </ul>   | Access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">EZView</a></li> <li>• iOS (iPhone): Free application <a href="#">EZView</a></li> </ul> | It is possible to operate via the Wi-Fi network from the mobile application on the iOS, Android systems : <ul style="list-style-type: none"> <li>• The <a href="#">Tuya Smart</a> free application on Android</li> <li>• The <a href="#">Tuya Smart</a> free application on iOS</li> </ul>  | ...   |
| Default IP address            | ...  | DHCP or 192.168.1.13  | ...   | ...   |
| Default admin user / password | ...  | admin / 123456  | ...   | ...   |
| Main features                 | <ul style="list-style-type: none"> <li>• Warning indication about exceeding the preset temperature,</li> <li>• schedule,</li> <li>• timer,</li> <li>• remote access,</li> <li>• voice control,</li> <li>• Pairing button,</li> <li>• Wi-Fi indicator,</li> <li>• Temperature history graph</li> </ul> ,<br>Settings memory after power failure <ul style="list-style-type: none"> <li>• For indoor use</li> <li>• Energy measurement - Charts and measurement history</li> </ul> | ...   | <ul style="list-style-type: none"> <li>• Sound signaling : 70 dB/m</li> <li>• LPG (propane-butane) gas - a gas heavier than air - The device should be mounted in low position, just above the floor</li> <li>• Natural gas (methane) - a gas lighter than air - The device should be mounted in high position, just under the ceiling</li> </ul> | <ul style="list-style-type: none"> <li>• The corrugation of the connection enables its bend,</li> <li>• Material : PCV,</li> <li>• UV radiation resistance</li> </ul> |
| Web browser access ports      | ...  | 80, 554   | ...   | ...   |
| PC client access ports        | ...  | Port no.: 80 or access by a cloud (P2P) - PC: Free application <a href="#">EZStation</a>  | ...   | ...   |
| Operation temp                | 0 °C ... 40 °C   | ...   | -10 °C ... 50 °C  | ...   |
| Mobile client access ports    | ...  | 80  | ...   | ...   |
| Port ONVIF                    | ...  | 80  | ...   | ...   |
| Permissible relative humidity | 5 % ... 90 % (non-condensing)  | ...   | ...   | ...   |
| RTSP URL                      | ...  | rtsp://192.168.1.13:554/unicast/c1/s0/live<br>- Main stream<br>rtsp://192.168.1.13:554/unicast/c1/s1/live<br>- Sub stream   | ...   | ...   |



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

|                       |   |   |                 |               |
|-----------------------|---|---|-----------------|---------------|
| Main features         | ...   | <ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 2D-DNR, 3D-DNR - Digital Noise Reduction</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• NAS - Network Attached Storage support</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Mirror - Mirror image</li> <li>• Privacy zones - max. 4</li> <li>• Motion detection with human/vehicle silhouette recognition</li> <li>• Sharpness - sharper image outlines</li> <li>• Intelligent image analysis : intrusion, crossing the line (tripwire)</li> </ul> | ...             | ...           |
| Power supply          | 85 ... 250 V  | <ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 500 mA</li> </ul>  | 85 ... 250 V AC | ...           |
| Power consumption     | ...   | ≤ 6 W   | ≤ 1.5 W         | ...           |
| Housing               | Plastic   | Compact, Metal + Plastic  | ...             | ...           |
| Color                 | White   | Black   | ...             | Black         |
| "Index of Protection" | ...   | IP67  | ...             | ...           |
| Vandal-proof          | ...   | —   | ...             | ...           |
| Operation temp        | ...   | -30 °C ... 60 °C  | ...             | ...           |
| Weight                | 0.1 kg - (total)  | 0.45 kg   | 0.05 kg         | ...           |
| Dimensions            | <ul style="list-style-type: none"> <li>• 93 x 55 x 30 mm</li> <li>• 95 cm (cable length) - Probe</li> </ul> | 190 73 x 71 mm  | Ø 48 x 75 mm    | Ø 40 x 215 mm |
| Supported languages   | ...   | Polish, English, Czech, Spanish, French, German, Portuguese, Slovak, Hungarian, Italian   | ...             | ...           |
| Manufacturer / Brand  | ATLO  | UNIVIEW   | ...             | ...           |
| Guarantee             | 2 years   | 3 years   | 2 years         | 2 years       |



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00