

	IP CAMERA BCS-L-TIP54FC-AI2 NightColor - 4 Mpx 3.6 mm	GPRS COMMUNICATION MODULE INT-GSM SATEL
		
	5307.65 CZK 5307.65 CZK	3070.39 CZK 3070.39 CZK
Standard	TCP/IP	...
Support	...	INTEGRA, INTEGRA Plus
Sensor	1/1.8 " Progressive Scan CMOS	...
Matrix size	4 Mpx	...
Scanning system	Progressive	...
Current consumption	...	< 130 mA (Standby mode) < 250 mA (operation)
Resolution	2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p	...
Lens	3.6 mm	...
View angle	<ul style="list-style-type: none"> • 93 ° (manufacturer data) • 90 ° (our tests result) 	...
Range of IR illumination	—	...
RS-485 interface	—	...
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	1 / 1	...
Audio	<ul style="list-style-type: none"> • External microphone input • Audio output • Bi-directional audio streaming support • Audio detection 	...
Main stream frame rate	25 fps @ 4 Mpx	...
Network interface	10/100 Base-T (RJ-45)	...
Network protocols	IPv4/IPv6, HTTP, HTTPS, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, SAMBA, PPPoE IEEE 802.1x, SNMP	...
Max. number of on-line users	20	...
ONVIF	20.06	...
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application BCS Manager • iOS (iPhone): Free application BCS Manager 	...
Default IP address	192.168.1.108	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80, 37777	...

PC client access ports	37777	...
WEB Server	Built-in, NVR compliance	...
Mobile client access ports	37777	...
Port ONVIF	80	...
RTSP URL	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...
Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • NightColor - colorful night mode • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • ICR - Movable InfraRed filter • BLC/HLC - Back Light / High Light Compensation • AGC - Automatic Gain Control • Possibility to change the resolution, quality and bit rate • Configurable Privacy Zones • Motion Detection • Mirror - Mirror image • Heat map - the selection in the image by corresponding colors the areas with different traffic • Intelligent image analysis : crossing the line (tripwire), intrusion, scene changing, abandoned/missing object, fast moving, illegal parking, detection of people gathering, loitering detection, face detection, people counting 	<ul style="list-style-type: none"> • Two SIM cards support • Possibility to check the pre-paid account balance • Time synchronization with the NTP server or GSM network • SMS, PUSH, e-mail (INTEGRA Plus) personal messaging • Remote control of the system state via mobile phone • User control with INTEGRA CONTROL - iOS / Android application • Monitoring GPRS, SMS • Cooperation with the ETHM-1 Plus Ethernet module allows using the GSM network as a backup communication path • Possibility of using the SATEL connection setup service • Programming control panels by using DLOADX (remote connection) • Supervision of the alarm system by using GUARDX (remote connection) • Connecting to the INTEGRUM system • Remote update of module software • Class II
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • ePoE, • 12 V DC / 320 mA 	12 V DC
Power consumption	≤ 3.8 W	...
Housing	Compact - Metal / Plastic	...
Color	White	...
"Index of Protection"	IP67	...
Operation temp	-30 °C ... 60 °C	...
Weight	0.92 kg	0.04 kg

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Dimensions	244 x 79 x 76 mm	80 x 57 x 15 mm
Supported languages	Polish, English	...
Manufacturer / Brand	BCS	SATEL
Guarantee	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00