




	ACCESS CONTROLLER ASC3202B DAHUA	ACCESS CONTROLLER DS- K2602T Hikvision	PLUG WT-L*P10
			
	537.59 USD 537.59 USD	635.49 USD 635.49 USD	2.44 USD 2.44 USD
Number of served transitions	2
Support	Cooperation with the access control systems
In package	10 pcs The price for package
Number of supported readers	<ul style="list-style-type: none"> • 2 pcs RS-485, • 2 pcs Wiegand 	<ul style="list-style-type: none"> • 4 pcs @ RS-485, • 4 pcs @ Wiegand 	...
Battery backup support	—	max. 7 Ah	...
Connector type	Ø 2.1 / 5.5 mm Straight plug
Alarm inputs / outputs	2 / 2
Wire mounting	Soldering
Length of the cable	0.21 m
Application	Electric cable
Material	PET
Example of application	<ul style="list-style-type: none"> • OMY-2X0.75 • K-60 • YAP
Input lines	...	<ul style="list-style-type: none"> • 4 pcs - Alarm inputs, • 2 pcs - Reed switch , • 2 pcs - Door/gate opening button, • 5 pcs - Tamper 	...
Output lines	...	<ul style="list-style-type: none"> • 2 pcs - Lock relay, • 4 pcs - Relay 	...
Network protocols	P2P, IPv4, DNS, DDNS, TCP, UDP, ONVIF CGI
Operation modes	<ul style="list-style-type: none"> • Main control mode • Sub control mode
Communication	<ul style="list-style-type: none"> • 3 x RS-485, • 2 x Wiegand 34/26, • 1 x Ethernet 10 / 100 Mbps (RJ-45) 	<ul style="list-style-type: none"> • RS-485, • Ethernet, • Wiegand (w26 / w34), • Open Supervised Device Protocol (OSDP) 	...
SAP Code	...	302913795	...

Main features	<ul style="list-style-type: none"> • Support for 2 doors (2x door sensor, 2x exit button, 2x alarm line, 2x lock control) • 1000 indexed users • Support up to 3000 finger prints • Memory of 5000 RFID cards • Support storage of 300 000 records • 128 General Purpose Schedules • Identification modes : RFID card, remote access, PIN, Fingerprint - Any combination of the above • Tamper protections • Automatic sending of alarm messages to the SmartPSS system or after entering a code, card or fingerprint defined as door opening under duress • Counter of the door opening time with the possibility of sending an alarm signal after exceeding the set value • Beep signal - Buzzer • White list, Black list • Web-Server built-in • Software update via network • Monitoring and configuration through network - SmartPSS Lite application • Power output 12 V DC / 1 A - supplying power to the lock • Support hardware I/O port configuration and export configuration diagrams • ONVIF compliance 	<ul style="list-style-type: none"> • 100000 indexed users • History of 300000 events • Remote programming from PC • Metal housing 	
Power supply	<ul style="list-style-type: none"> • 12 V DC / 2.5 A • PoE (802.3at) 	100 ... 240 V AC	...
Power consumption	<ul style="list-style-type: none"> • ≤ 2 W (standby) • max. 20.4 W @ 12 V (operation) • max. 14.4 W @ PoE (operation)
Housing	Plastic (PC + ABS)
Color	White

IK rating	IK06
Operation temp	-10 °C ... 55 °C	-20 °C ... 65 °C	...
Permissible relative humidity	5 % ... 95 % (non-condensing)	10 % ... 90 % (non-condensing)	...
Weight	0.72 kg	4.6 kg	0.020 kg
Dimensions	186 x 186 x 58 mm	373 x 345 x 98 mm	...
Manufacturer / Brand	DAHUA	Hikvision	...
Guarantee	3 years	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00