



	POWER DISTRIBUTION UNIT PR-1.5M-3G-SW/USB/W (3 OUTLETS + 2 USB) 1.3 m	INSULATION RESISTANCE METER + RCD TESTER UT-582+ UNI-T
		
	12.99 AUD 12.99 AUD	223.43 AUD 223.43 AUD
Rated voltage	220 ... 240 V AC / 50 Hz	...
AC voltage measurement	...	30 V ... 600 V \pm (3% + 3) @ 1 V
Total maximal current	10 A	...
Maximal total load	2500 W	...
Frequency measurement	...	45 Hz ... 65 Hz - frequencies displayed are for illustrative purposes
Number of outlets	<ul style="list-style-type: none"> • 3 grounded outlets 10A/250V CEE 7/5, • 2 USB ports 2.1A/5V 	...
Fuse	—	...
Switch	✓	...
Wire gauge	3 x 1.5 mm ²	...
Length of the cable	1.3 m	...
Housing	Plastic	...
Color	White	...
Test of RCDs	...	<ul style="list-style-type: none"> • Working voltage: 220V \pm 10 % • Test current: 10mA / 20mA / 30mA / 100mA / 300mA / 500mA • Switch-off time ranges : <ul style="list-style-type: none"> - x 1/2 - 10 / 20 / 30 / 100 / 300 / 500 mA @ 2000 ms - x 1 - 10 / 20 / 30 / 100 / 300 mA @ 1000 ms - x 5 - 500 mA @ 300 ms - AUTO RAMP - 10 / 20 / 30 / 100 / 300 / 500 mA @ 300 ms • AUTO RAMP test: measurement of shutdown current (with simultaneous measurement of time)
Automatic change of measuring ranges	...	—
RS-232	...	—
USB	...	—

Main features	...	<ul style="list-style-type: none"> • Phase switch 0° / 180° during RCD test, • Large, readable LCD display with backlight, • Buzzer, • Low battery level alarm, • Aesthetic and solid construction
Operation temp	...	0 °C ... 40 °C
Permissible relative humidity	...	≤ 80 % (non-condensing)
Power supply	...	6 x 1.5V, type AA/LR6/FR6 battery - included
Weight	0.32 kg	0.380 kg
Dimensions	202 x 49 x 40 mm	160 x 100 x 69 mm
Manufacturer / Brand	...	UNI-T
Guarantee	2 years	2 years