

| | | | |
|----------------------------|--|---|---|
| | ACCESS POINT 4G+ LTE Cat. 6 +ROUTER ARCHER-MR600 Wi-Fi 2.4 GHz, 5 GHz 867 Mbps + 300 Mbps TP-LINK | BRACKET RG-RAP1200(P)-MNT REYEE | HDD ENCLOSURE MCE-582 SSD M.2 SATA MACLEAN |
| |  |  |  |
| | 150.61 EUR 150.61 EUR | 37.07 EUR 37.07 EUR | 14.29 EUR 14.29 EUR |
| Frequency range | 2.4 GHz , 5 GHz | ... | ... |
| In package | ... | 10 pcs The price for package | ... |
| Application | ... | RG-RAP1200(P) | ... |
| Material | ... | Plastic | ... |
| Supported hard drives | ... | ... | 1 x M.2 SATA III : 2230 / 2240 / 2260 / 2280 |
| Color | ... | White | ... |
| Antenna type | WiFi - built-in , 2 x 4G LTE | ... | ... |
| Outputs | ... | ... | 1 x USB 3.0 Micro B, max. 5 Gb/s |
| Standards | <ul style="list-style-type: none"> • IEEE 802.11 b/g/n, • IEEE 802.11 a/n/ac | ... | ... |
| Operation state indication | ... | ... | LED diodes |
| Housing | ... | ... | Plastic |
| Baud rates | <ul style="list-style-type: none"> • 5 GHz : 867 Mbps (max) + • 2.4 GHz : 300 Mbps (max) • LTE : 300 Mbps | ... | ... |
| LAN ports | <ul style="list-style-type: none"> • 1 x 10/100/1000 Mbps - LAN/WAN • 3 x 10/100/1000 Mbps - LAN | ... | ... |
| Receiver sensitivity | 5 GHz : <ul style="list-style-type: none"> • 11a 54M: -74dBm • 11ac HT20: -66 dBm • 11ac HT40: -63 dBm • 11ac HT80 : -59 dBm • 11n HT20: -73dBm • 11n HT40: -70dBm 2.4 GHz : <ul style="list-style-type: none"> • 11g 54M: -74dBm • 11n HT20: -72 dBm • 11n HT40: -69 dBm | ... | ... |
| LTE | ✓ | ... | ... |
| QSS | — | ... | ... |

| | | | |
|-------------------------------|--|--|------------------------|
| WDS | ✓ | ... | ... |
| Transmitter power | max. 23 dBm | ... | ... |
| Main features | <ul style="list-style-type: none"> • IP-layer bandwidth control mechanism • Local, remote or via TP-Link Cloud management • Support for TP-Link OneMesh™ technology • SIM socket • WPS/RESET button | <ul style="list-style-type: none"> • Wall mounting • The product fits into mounting boxes compliant with US/EU standards | ... |
| Power supply | 12 V DC / 1.5 A (power adapter included) | ... | 5 V DC - from USB port |
| Operation temp | 0 °C ... 40 °C | ... | ... |
| Permissible relative humidity | 95 % (non-condensing) | ... | ... |
| Weight | 0.478 kg | 0.1 kg | 0.05 kg |
| Dimensions | 230 x 163 x 37 mm | 126 x 86 x 4 mm | 118 x 40 x 9 mm |
| Manufacturer / Brand | TP-LINK | RUIJIE / REYEE | MACLEAN |
| Guarantee | 3 years | 2 years | 2 years |