

	EXTENDER TRANSMITTER HDMI-EX-150IR/TX-V4	AC POWER SUPPLY ADAPTER AWT-682 PULSAR	KEYBOARD MODULE VTO4202F-MB2 FOR MODULE VTO4202F-P DAHUA
			
	929.41 NOK 929.41 NOK	319.62 NOK 319.62 NOK	680.93 NOK 680.93 NOK
Compatibility	VTO4202F-P
Device type	Transmitter
Adapter type	...	Transforming	...
HDMI standard	1.3
Power voltage	...	230 V AC	...
HDCP	1.4
Frequency range	...	50 Hz	...
Protocols	HdbitT
Power consumption	≤ 1 W
Output voltage	...	<ul style="list-style-type: none"> • 18 V AC, • 20 V AC 	...
Housing	Metal + Plastic, Waterproof
Color	Silver
Supported HDMI resolutions	1080p, 1080i, 720p, 576p, 576i, 480p, 480i
Maximal load	...	<ul style="list-style-type: none"> • 3.3 A @ 18 V AC, • 3 A @ 20 V AC 	...
Environment class	...	II	...
Vandal-proof	IK07
"Index of Protection"	...	IP43	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone
Output power	...	60 VA	...
Application	...	<ul style="list-style-type: none"> • to alarm systems powering • to automatic systems • to low-voltage light installation powering 	...
Output	...	2 pcs	...
Maximal transmission range	<ul style="list-style-type: none"> • 120 m @ 1080p - UTP cat. 6 • 100 m @ 1080p - UTP cat. 5e • 80 m @ 1080p - UTP cat. 5
Manufacturer / Brand	...	PULSAR	DAHUA

Main features	<ul style="list-style-type: none"> • IR carrier frequency : 20 ... 60 kHz • Baudrate : 18 Mbps • Protections : lightning, Overvoltage, ESD 	...	Doorbell button - 2 pcs
Power supply	5 V DC / 1 A - (power adapter included)	...	5 V DC - Supplied from other modules
Current consumption	3 W
Operation temp	0 °C ... 60 °C	...	-20 °C ... 60 °C
Weight	0.146 kg	1.29 kg	0.1 kg
Dimensions	97 x 94 x 24 mm	124 x 75 x 65 mm	100 x 49.9 x 30.5 mm
Guarantee	2 years	2 years	3 years