






	<a href="#">COUPLER WW-5.5</a>	<a href="#">OUTDOOR TWISTED PAIR CABLE FTP/K5/LN/100M NETSET</a>	<a href="#">ISOPROPYL ALCOHOL CLEANSER-IPA/100 BOTTLE 100 ml</a>	<a href="#">MODULAR CONTACTOR KMC-63-40 63 A 400 V AC IDEAL</a>	<a href="#">CLEANING PASTE PEVALIN-PROFESSIONAL/250 TUBE 250 ml TESA</a>
					
	1.98 PLN 1.98 PLN	2.31 PLN 2.31 PLN	11.50 PLN 11.50 PLN	94.77 PLN 94.77 PLN	33.80 PLN 33.80 PLN
Package	...	...	Bottle 100 ml	...	Tube 250 ml
Device type	...	...	...	Contactor - NO, Three-phase	...
In section	...	<b>100 m . Price for 1m when buying a whole roll</b>	...	...	...
Connector type	Coupler Plug 2.1 : 5.5 mm / Plug 2.1 : 5.5 mm	...	...	...	...
Type	...	FTP cat. 5e Shielded + Messenger wire	...	...	...
Material	Metal / PET	...	...	...	...
Nominal load current	...	...	...	• 63 A @ AC7A / AC1, • 25 A @ AC7B	...
Inner conductor	...	Ø 0.5 mm, AWG 24, Cu wire	...	...	...
Rated load voltage	...	...	...	400 V AC	...
Nominal power voltage	...	...	...	230 V AC	...
Resistance	...	9.5 Ω / 100 m	...	...	...
Nominal power	...	...	...	• 40000 W @ 400 V AC7A • 13000 W @ 400 V AC7B	...
Number of NO/NC contacts	...	...	...	4 / 0	...
Shield	...	Polyester foil, Al foil	...	...	...
Outer coating	...	Ø 6.2 mm LDPE	...	...	...
Category of use	...	...	...	AC1, AC7A, AC7B	...
Connectors type	...	...	...	screw terminals	...
Coating color	...	Black	...	...	...
Supported norms	...	EN 50575:2014	...	...	...
Main features	<ul style="list-style-type: none"> <li>• Very easy and quick assembly</li> <li>• Corrosion resistance</li> </ul>	<ul style="list-style-type: none"> <li>• Messenger wire Ø 1.2 mm</li> <li>• UV radiation resistant, moisture and water resistant</li> <li>• Parameters far exceeding the requirements for Category 5e</li> </ul>	...	<ul style="list-style-type: none"> <li>• Operation temp : -25 °C ... 40 °C</li> <li>• Supported norms : PN-EN 60947-4-1, PN/EN 61095</li> </ul>	...
Operation temp	...	-20 °C ... 70 °C	...	...	...
Housing	...	...	...	Plastic, DIN, TH-35 rail mounting	...
"Index of Protection"	...	...	...	IP20	...
Width in 17.5 mm modules	...	...	...	3	...
Weight	0.002 kg	...	0.09 kg	0.32 kg	...
Dimensions	Ø 12 x 40 mm	...	Ø 50 x 105 mm	67 x 81 x 54.7 mm	...
Manufacturer / Brand	...	NETSET	...	IDEAL	TESA
Guarantee	2 years	15 years	...	5 years	2 years