



	<a href="#">ACCESS CONTROLLER ASC2204B-S DAHUA</a>	<a href="#">ACCESS CONTROLLER PR311SE-BK ROGER</a>
		
	3331.45 NOK 3331.45 NOK	1269.39 NOK 1269.39 NOK
Number of served transitions	4 (one-way)	...
Cards support	...	Unique EM 125kHz
Support	DAHUA	...
Reading distance of prox-keys	...	max. 15 cm
Number of supported readers	4 pcs	...
Keyboard built-in	...	—
Battery backup support	—	...
Output lines	5 pcs - Relay	...
Selected features of the standalone mode	...	<ul style="list-style-type: none"> <li>• 1000 indexed users</li> <li>• Operation with XM-2 I/O extension module (Full Standalone Mode)</li> </ul>
Communication	<ul style="list-style-type: none"> <li>• RS-485,</li> <li>• Ethernet,</li> <li>• Wiegand</li> </ul>	<ul style="list-style-type: none"> <li>• RS-485</li> <li>• RACS (Roger)</li> </ul>
Default IP address	192.168.0.2	...
Default admin user / password	admin / - The administrator password should be set at the first start	...

Main features	<ul style="list-style-type: none"> <li>• 100000 indexed users</li> <li>• History of 150000 events</li> <li>• Remote programming from PC</li> <li>• Function of protection against multiple use of the same card for access (anti-passback)</li> <li>• Counter of the door opening time with the possibility of sending an alarm signal after exceeding the set value</li> <li>• Automatic sending of alarm messages to the SmartPSS system or after entering a code, card or fingerprint defined as door opening under duress</li> </ul>	<ul style="list-style-type: none"> <li>• The ability to add additional reader (bilateral way door control),</li> <li>• 3 programmable input lines NO/NC,</li> <li>• 2 programmable transistor outputs 1A,</li> <li>• One programmable relay output 1.5A/30V,</li> <li>• Door modes (Normal, Locked, Unlocked and Conditionally Unlocked),</li> <li>• Any topology of communication bus,</li> <li>• "Guest" type additional users support defined individually on each controller,</li> <li>• Integration with an alarm system via in/out line ,</li> </ul>
Power supply	12 V DC / 1.4 A	10 ... 15 V DC
Average current consumption	...	50 mA
Operation temp	-30 °C ... 60 °C	-25 °C ... 60 °C
Permissible relative humidity	max. 95 % (non-condensing)	10 ... 95 % (non-condensing)
Weight	0.354 kg	0.18 kg
Dimensions	207 x 116 x 52 mm	152.5 x 46 x 23 mm (Standard housing stand) 152.5 x 46 x 35 mm (Thicker housing stand)
Manufacturer / Brand	DAHUA	ROGER
Guarantee	3 years	3 years