



	ROUTER RUT301 Teltonika	ADAPTER AD-UTP 2x RJ45 / 1x RJ45
		
	1549.79 CZK 1549.79 CZK	93.16 CZK 93.16 CZK
LAN ports	4 x 10 / 100 Mbps	...
Connectors type	...	<ul style="list-style-type: none"> • 2 x RJ-45 shielded socket • 1 x RJ-45 plug - Shielded
Length of the cable	...	12 cm
WAN interface	1 x 10 / 100 Mbps	...
LED indicators	Power, WAN, LAN	...
Port USB	USB 2.0	...
DHCP server	✓	...
DDNS	Support > 25	...
Protections	<ul style="list-style-type: none"> • IEEE 802.1x and Radius Authentication • MAC addresses filtering • Firewall • Support DDOS, SYN, SSH, HTTP/HTTPS defence • White list / Black list 	...
Management interface	Web browser, Teltonika RMS application	...
Default IP address	192.168.1.1	...
Operating system	RutOS (Linux OS based)	...
Firmware update	✓	...

Main features	<ul style="list-style-type: none"> • Compliance with the Modbus, DLMS, DNP3, OPC UA protocol • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Static / dynamic routing • Support for VoIP technology, • View topology and network status • WMM support (QoS mechanism of the 802.11e standard) • DHCP Relay support • Load balance • VLAN support • VPN networks: IPsec VPN, L2TP VPN, PPTP VPN, Open VPN • Compliance with the MQTT protocol • SNMP v1/v2/v3/Trap • Support for IoT (Internet of Things) systems, • Configuration using the Teltonika RMS application • Communication interface - Port USB 2.0 - possibility to connect external HDD, flash drive, additional modem, printer, USB-serial adapter • 2 digital inputs / outputs - ability to set certain I/O conditions to initiate event, • RESET button • Durable aluminum housing • Shock-proof • Industrial wide temperature design. • 4-pin industrial power socket, • Wide range of supported supply voltages • "Index of Protection" : IP30 • Ethernet cable included 	...
Certificates	CE, UKCA, FCC, WEEE	...
Power supply	<ul style="list-style-type: none"> • 9 ... 30 V DC • 9 V DC / 1 A (power adapter included) 	...
Power consumption	≤ 3.8 W	...
Operation temp	-40 °C ... 75 °C	...



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Permissible relative humidity	10 % ... 90 % (non-condensing)	...
Weight	0.23 kg	0.04 kg
Dimensions	100 x 90 x 30 mm	50 x 37 x 21 mm
Manufacturer / Brand	Teltonika	...
Guarantee	2 years	2 years