



	INSULATION RESISTANCE METER + RCD TESTER UT-582+ UNIT	POWER DISTRIBUTION UNIT MCE-10 (10 OUTLETS) 1.5 m MACLEAN
		
	137.56 EUR 137.56 EUR	13.61 EUR 13.61 EUR
Rated voltage	...	230 V AC / 50 Hz
Total maximal current	...	16 A
AC voltage measurement	30 V ... 600 V \pm (3% + 3) @ 1 V	...
Maximal total load	...	3680 W
Frequency measurement	45 Hz ... 65 Hz - frequencies displayed are for illustrative purposes	...
Number of outlets	...	2 x 5 grounded outlets 16A/250V, E type (CEE 7/5)
Fuse	...	16 A / 250 V
Switch	...	2 pcs - illuminated, each for a section of 5 outlets
Wire gauge	...	3 x 1.5 mm ²
Length of the cable	...	1.5 m
Housing	...	Plastic
Color	...	Black
Test of RCDs	<ul style="list-style-type: none"> • Working voltage: 220V \pm 10 % • Test current: 10mA / 20mA / 30mA / 100mA / 300mA / 500mA • Switch-off time ranges : <ul style="list-style-type: none"> - x 1/2 - 10 / 20 / 30 / 100 / 300 / 500 mA @ 2000 ms - x 1 - 10 / 20 / 30 / 100 / 300 mA @ 1000 ms - x 5 - 500 mA @ 300 ms - AUTO RAMP - 10 / 20 / 30 / 100 / 300 / 500 mA @ 300 ms • AUTO RAMP test: measurement of shutdown current (with simultaneous measurement of time) 	...
Automatic change of measuring ranges	—	...
RS-232	—	...
USB	—	...

Main features	<ul style="list-style-type: none"> • Phase switch 0° / 180° during RCD test, • Large, readable LCD display with backlight, • Buzzer, • Low battery level alarm, • Aesthetic and solid construction 	...
Operation temp	0 °C ... 40 °C	...
Permissible relative humidity	≤ 80 % (non-condensing)	...
Power supply	6 x 1.5V, type AA/LR6/FR6 battery - included	...
Weight	0.380 kg	0.968 kg
Dimensions	160 x 100 x 69 mm	738 x 70 x 45 mm
Manufacturer / Brand	UNI-T	MACLEAN
Guarantee	2 years	2 years