

	WLAN USB ADAPTER ARCHER-T3U 300 Mbps @ 2.4 GHz, 867 Mbps @ 5 GHz TP-LINK	TOOL FOR CLEANING FIBER OPTIC CONNECTORS WUN-015 MU / LC	WIRELESS VIDEO DOORBELL ATLO-DBCT-TUYA-V2 Wi-Fi, Tuya Smart
			
	23.14 EUR 23.14 EUR	21.51 EUR 21.51 EUR	48.59 EUR 48.59 EUR
Sensor	CMOS - 2 Mpx
Resolution	1920 x 1080 px - 1080p
Application	...	Ideal for removing dirt from optical components Connector type : MU / LC	...
Lens	3.6 mm
Supported standards	IEEE 802.11 b/g/n @ 2.4 GHz , IEEE 802.11 a/n/ac @ 5 GHz
View angle	• 120 ° (manufacturer data) • 98 ° (our tests result)
IR illuminator	✓
LED illuminator	—
Supported transmission speeds	300 Mbps @ 2.4 GHz , 867 Mbps @ 5 GHz
Wireless transmission range	The range limited only by the availability of the Wi-Fi network
Operation modes	Ad-Hoc, Infrastructure
Wi-Fi standard	2.4 GHz IEEE 802.11 b/g/n
Network interface	2.4 GHz Wi-Fi
Mobile phones support	The Tuya Smart free application on Android The Tuya Smart free application on iOS
Modulation	DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM, 256-QAM
Antenna type	Omnidirectional antenna , Integrated
Interface	USB
Frequency range	2.4 GHz ... 2.4835 GHz , 5.15 GHz ... 5.85 GHz
Transmitter power	< 20 dBm

Receiver sensitivity	<ul style="list-style-type: none"> • 2.4 GHz : 11b 11M : -86 dBm 11g 54M : -65 dBm 11n HT20 : -71 dBm 11n HT40 : -70 dBm • 5 GHz : 11a 6M : -91 dBm 11a 54M : -76 dBm 11n HT20 : -71 dBm 11n HT40 : -70 dBm 11ac HT20 : -68 dBm 11ac HT40 : -64 dBm 11ac HT80 : -62 dBm
Main features	<p>Doorbell button + Camera</p> <ul style="list-style-type: none"> • The microSD cards support 128 GB - Video recording to micro SD card, • Motion Detection - PIR detector, • ICR - Movable InfraRed filter, • Microphone built-in, • Speaker built-in, • Bidirectional communication, • Full support via network : WiFi, • Possibility to work in cloud - you don't need to redirect the ports, • Video PUSH personal messaging • Increased battery life • Low current consumption <p>Wireless doorbell</p> <ul style="list-style-type: none"> • Operating frequency 433 MHz • Volume ≤ 100 dB • Selecting the ringer melody • Number of ring-tones : 60 • 5-level ring tone volume adjustment • LED indicator
Mount	Surface-mounted
Security measures	WEP 64/128-bit, WPA/WPA2, WPA-PSK/WPA2-PSK
Included drivers	Windows XP/Vista/7/8/10/11

Certificates	CE, FCC, RoHS
Operation temp	0 °C ... 40 °C
Manufacturer / Brand	TP-LINK
Power supply	Doorbell button + Camera <ul style="list-style-type: none"> • 2 x 18650 battery 3.7 V / 3200 mAh (not included) • Charging via micro USB port 5 V DC (cable included) Wireless doorbell <ul style="list-style-type: none"> • 90 ... 260 V AC
Power consumption	0.15 W (operation), ≤ 10 mW (Standby mode) - Wireless doorbell
Housing	Plastic
Color	White / Black
Weight	...	0.02 kg	<ul style="list-style-type: none"> • 0.128 kg - Doorbell button + Camera • 0.050 kg - Wireless doorbell
Dimensions	40.5 x 19.72 x 10.29 mm	183 x 18 x 18 mm	<ul style="list-style-type: none"> • 145 x 51 x 38 mm - Doorbell button + Camera • 70 x 51 x 68 mm - Wireless doorbell
Guarantee	3 years	...	2 years