

	HANDS-FREE SWITCH AD-TL-6497/P-S 5 V - 24 V DC ORNQ	SMART CONTROLLER FOR ROLLER SHUTTERS SRW-02M-WI-FI 230 V AC ZAMEL	CLEANING PASTE PEVALIN-PROFESSIONAL/500 500 ml TESA	CYLINDRICAL MAGNETIC CONTACT S-3 SATEL	UPS AT-UPS3000/2-LCD 3000 VA EAST	CABLE OUTLET DPK1.01/49-SIMON54	SWITCHING ADAPTER 12V/1A/5.5
							
	5.25 USD 5.25 USD	103.07 USD 103.07 USD	12.95 USD 12.95 USD	9.37 USD 9.37 USD	700.79 USD 700.79 USD	7.26 USD 7.26 USD	4.25 USD 4.25 USD
Power adapter type	Online
Model identifier	12V/1A/5.5
Detection	Opening the door or window
Nominal power	2700 W
Support	...	SUPLA	Simon 54 product series, for Nature, Premium frames	...
Application	Works with LED lighting	roller shutters, roof windows, awnings, drop-down screens, curtains
Maximum reed switched voltage	20 V
Package	500 ml
Apparent Power	3000 VA
Number of modules	1	...
Maximal switched current	20 mA
Make distance	15 mm
Input voltage	230 V AC ± 25 %	...	100 - 240 V AC
AC input frequency	50 / 60 Hz
Break distance	24 mm
Input frequency	50 / 60 Hz (auto detection)
Output current	1.0 A
Output power	12.0 W
Rated voltage	5 V - 24 V DC	230 V AC
Output voltage	230 V AC ± 5 % (Pure Sine Wave)	...	12.0 V DC
Average efficiency during work	83.0 %
Maximal total load	• 5 V = 40 W • 12 V = 96 W • 24 V = 120 W
Relay maximal load	...	5 A
Efficiency at low load (10%)	67.1 %
Total maximal current	8 A
Output frequency	50 / 60 Hz
No-load power consumption	< 0.10 W
Maximal outputs load	...	350 W (single output)
Adapter type	Switching
Voltage adjustment	± 1 %
Output voltage adjustment	—
Detection range	10 mm ... 60 mm
Detection method	Passive Infra Red (PIR)
Frequency adjustment	—
Number of inputs	0	4
Transfer time	4 ms
Charging time (recover to 90% capacity)	8 hours
Power connectors type	• 230 V Plug • 12 V - 2.1/5.5 mm Straight plug
Connector type	PCB (soldering)	screw terminals
Battery	8 pcs - 12V/7Ah
Wireless	—	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n
Length of the cable	1 m
Mobile phones support	—	• The SUPLA free application on Android • The SUPLA free application on iOS
Housing	—	Plastic	Non-halogen plastic, PC	...
"Index of Protection"	IP20	IP20	IP20	...
Color	—	Green	...	Silver	...	Matt black	...
Operation temp	...	-10 °C ... 55 °C
Estimated battery operation time	• 28.5 minutes @ 600 W, • 18 minutes @ 800 W, • 11.5 minutes @ 1000 W, • 9 minutes @ 1200 W, • 6 minutes @ 1600 W, • 3.5 minutes @ 2000 W, • 3 minutes @ 2700 W
Number of outputs	1	2 (Motors)	• 2 pcs CEE 7/3 (Schuko), • 3 pcs IEC-320 C13	...	1 pcs

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Management software	UPSsmart (Windows 95/98/2000/XP/Vista/7/8/10, Linux)
Protections	<ul style="list-style-type: none"> • Fuse • Overvoltage • Overload protection • Overcharge protection • EPO (Emergency power off) switch • Ethernet filter 	...	Overload
Operation state indication	<ul style="list-style-type: none"> • LCD display: operation mode, battery charging level, in/out voltage level, overload indicator, • Sound signaling
Main features	<ul style="list-style-type: none"> • High power - max. 120 W • Possibility to adjust the light intensity depending on your needs • Works with lampshades made of plastic • Small dimensions • Possible assembly in a profile • Simple and quick device installation 	<ul style="list-style-type: none"> • Local control by physical button, • schedule, • timer, • remote access, • voice control, • Possibility to manually program scenarios from the built-in API 	...	<ul style="list-style-type: none"> • Aluminum • Tamper signaling 	<ul style="list-style-type: none"> • Auto restart while AC is recovering • Automatic Voltage Regulator (AVR) • "Cold Start" function • Compatible with power generators • Remote management - UPSsmart application included • Built-in EMI, RFI filter • Excellent microprocessor control guarantees high reliability • self test feature • Battery charge and maintenance control • USB/RS-232 communication port 	<ul style="list-style-type: none"> • Cable diameter : 6.2 ... 14.5 mm • Claw or screw mounting • Installation in flush-mounted enclosures • Aesthetic and solid construction 	...
Application	<ul style="list-style-type: none"> • Surveillance Systems • data storage centers • network, servers, workstations • Industrial Equipment
Housing type	Tower	...	Casing with plug
Operation temp. / Relative humidity	0 °C ... 40 °C / 0 ... 90 %
Weight	0.001 kg	0.127 kg	...	0.043 kg	27 kg	0.05 kg	0.125 kg
Dimensions	49 x 10 x 4 mm	90 x 66 x 35 mm	...	36.3 x 8.6 x 11 mm	460 x 191 x 332 mm	<ul style="list-style-type: none"> • 75 x 75 x 55 mm • 22 mm - mounting depth 	80 x 55 x 75 mm
Manufacturer / Brand	ORNO	ZAMEL	TESA	SATEL	EAST	KONTAKT Simon	...
Guarantee	2 years	2 years	2 years	2 years	2 years	6 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00