




	POWER DISTRIBUTION UNIT ACAR-S8/FA/RACK	FURNITURE POWER DISTRIBUTION UNIT FPS-2S2U/CABLE (2 OUTLETS + 2 USB)	RFID PROXIMITY CARD ATLO-104N13
			
	31.74 USD 31.74 USD	33.57 USD 33.57 USD	0.44 USD 0.44 USD
Standard	Unique EM 125kHz
Compatibility	EM4100/4102
Rated voltage	230 V AC / 50 Hz	230 V AC / 50 Hz	...
Possibility of programming the serial number (ID)	—
Total maximal current	...	16 A	...
Nominal load current	10 A (total)
Ability to write to internal memory	—
Maximal total load	...	3680 W	...
Serial Number overprint	✓
Nominal voltage of surge suppressor	250 V / 50 Hz
Protection level of surge suppressor	≤ 1.3 kV (L/N)
Fuse	...	—	...
Number of outlets	8 grounded outlets 10A/250V	2 grounded outlets 16A/250V CEE 7/5, (Schuko)	...
Automatic delayed fuse	✓
Nominal stroke current	2 kA (L/N) - 8/20 μs
Maximum stroke current	6.5 kA (L/N) - 8/20 μs
Leak current	< 0.5 mA
Response time	< 25 ns
Main features	...	<ul style="list-style-type: none"> • Fixing in the opening of the table top • Pull-out panel with sockets at the push of a button • 2 x USB socket 5 V / 2 A 	<ul style="list-style-type: none"> • Serial Number Format : 10H13D + WEG24A • Range : ~ 11 cm • The TK-4100 chip
Switch	two-way, with light indication	—	...
Manufacturer / Brand	ATLO
Length of the cable	2.9 m	1.8 m	...
"Index of Protection"	...	IP20	...
Housing	RACK 19", 1U, Plastic - non-flammable	Plastic + Aluminum, Steel - powder painted	...
Color	...	Silver + Black	...

Weight	0.61 kg	1.47 kg	0.006 kg
Dimensions	445 x 54 x 55 mm	<ul style="list-style-type: none"> • 265 x 120 x 77 mm • 250 x 110 x 66 mm - Mounting dimensions (box)	86 x 54 x 1 mm
Guarantee	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00