



	FLUSH-MOUNTING DISTRIBUTION CABINET 24-MODULAR LE-602432 RWN LEGRAND	BUFFERED POWER SUPPLY TRANSFORMER AWZG2-12V2A-B PULSAR
		
	49.52 EUR 49.52 EUR	88.42 EUR 88.42 EUR
Adapter type	...	Transforming
Method of mounting	Flush-mounted	...
Input voltage	...	230 V AC
Output voltage	...	11.0 V ... 13.8 V (buffer operation)
Max. output current (total)	...	2 A
Number of mounted modules	12 + 1 x 2 rows, 17.5 mm	...
Spacing between TH 35 rails	125 mm	...
Transparent door	—	...
Battery charging current	...	0.2 A / 0.5 A (set with the JP1 jumper)
Power	...	27 W
Number of outputs	...	1
Protections	...	<ul style="list-style-type: none"> • Short-circuit • Overload • Overvoltage • Overheat • Tamper • Reverse polarity connection • Discharge
Adapter operation control	...	<ul style="list-style-type: none"> • AC input voltage presence indication AC • DC output voltage presence indication DC • No battery or fail battery • Battery charging - on the mainboard • EPS FLT output - indicating AC power collapse • APS FLT output - Battery fault indication

Equipment	<ul style="list-style-type: none"> • Terminal blocks 3 x (4 x 16 mm² + 4 x 10 mm²) 1 x (11 x 16 mm² + 11 x 10 mm²) • Module blanking plates : 1 x 5 pcs 	...
Material	Self-extinguishing	...
Color	White	...
"Index of Protection"	IP40	...
IK rating	IK07	...
Compliance with standards	PN-EN 60439-3, IEC/EN 61439-3	...
Main features	<ul style="list-style-type: none"> • 6 mm thick metal door • The door can be equipped with a lock • Removable top and bottom panel • Equipped with terminal blocks and modules blanking plates 	<ul style="list-style-type: none"> • Output voltage - stabilized • Microprocessor-based automation system • Battery charge and maintenance control • Tamper signaling - NC • LED indication • 2 x OC output • Compliance to EN 50131-6:2017 @ Grade 2 standard • Compliance to EN 60839-11-2:2015+AC:2015 @ Grade 2 standard
Place for battery	...	12 V / 9 Ah (max)
Max. battery dimensions	...	190 x 100 x 75 mm
Weight	3.05 kg	2.02 kg
Dimensions	350 x 460 x 93 mm , 330 x 430 x 87 mm - flush-mounting box	205 x 237 x 90 mm
Manufacturer / Brand	LEGRAND	PULSAR
Guarantee	2 years	5 years