





	<a href="#">SWITCH POE IPB-5-10A-S4 5-PORT ATTE</a>	<a href="#">TV OR MONITOR MOUNT BRATECK-LPA52-466</a>	<a href="#">SEPARATOR WITH VIDEO BALUN D-SEP/HD-4/TR</a>
			
	126.58 AUD 126.58 AUD	25.33 AUD 25.33 AUD	39.54 AUD 39.54 AUD
LAN ports	<ul style="list-style-type: none"> <li>• 1 x RJ45 10/100 Base-T - Uplink</li> <li>• 5 x RJ45 10/100 Base-T - PoE (802.3af/at) / Passive PoE</li> </ul>	...	...
Mounting standard	...	VESA : 75, 100, 200, 300, 300x200, 400x200, 400, 600x200, 600x400	...
Standard	...	...	<ul style="list-style-type: none"> <li>• AHD - 8 Mpx, 4K UHD</li> <li>• HD-CVI - 8 Mpx, 4K UHD</li> <li>• HD-TVI - 8 Mpx 4K UHD</li> <li>• CVBS - PAL / NTSC</li> </ul>
Management	—	...	...
Screen size range	...	37 " ... 70 "	...
Bearing capacity	...	40 kg	...
LED diodes	Power, LAN	...	...
Distance from mounting surface	...	53 ... 464 mm	...
Color	...	Black	...
Transmission speed	10 / 100 Mbps : 1 Port LAN + 5 LAN & PoE ports	...	...
Tilt adjustment	...	-15 ° ... 5 °	...
Horizontal rotation	...	-60 ° ... 60 °	...
Rotation in the plane of the screen	...	-3 ° ... 3 °	...
Video transmission range	...	...	<ul style="list-style-type: none"> <li>• 250 m @ 720p - UTP cat. 5e</li> <li>• 150 m @ 1080p - UTP cat. 5e</li> <li>• 400 m @ CVBS - PAL / NTSC - UTP cat. 5e</li> </ul>
Device type	...	...	Passive
Number of channels	...	...	4 pcs Video
Number of inputs	...	...	4 pcs cable terminals
Number of outputs	...	...	4 pcs BNC socket
Maximal output power	<ul style="list-style-type: none"> <li>• 40 W @ Passive PoE - 1 ... 5 ports,</li> <li>• 30 W @ PoE (802.3at) - 1 ... 5 ports</li> <li>• 15.4 W @ PoE (802.3af) - 1 ... 5 ports</li> </ul>	...	...

Maximal total power	90 W	...	...
Input impedance	...	...	100 $\Omega$
Output impedance	...	...	75 $\Omega$
Opto-isolation between inputs and outputs	...	...	50 V DC
Galvanic separation between individual channels	...	...	> 2000 V
Main features	<ul style="list-style-type: none"> <li>• Supported PoE devices: 802.3af/at, Passive PoE</li> <li>• Possibility to connecting in cascade</li> <li>• Efficiency : 93 % @ 90 W</li> <li>• 5 polymer fuses - PoE</li> <li>• Possibility to power other devices powered from 55 V (screw connection)</li> <li>• PSU thermal protection</li> <li>• Short-circuit protection</li> <li>• Overload protection</li> <li>• The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 4 ports</li> <li>• Switch has built-in a 55 V DC power supply adapter with power of 90 W</li> <li>• "Index of Protection" : IP55</li> </ul>	...	...
Attenuation	...	...	<ul style="list-style-type: none"> <li>• 4.43 MHz @ 0.34 dB</li> <li>• 11 MHz @ 0.49 dB</li> <li>• 21 MHz @ 0.71 dB</li> <li>• 38 MHz @ 1.00 dB</li> <li>• 42 MHz @ 1.08 dB</li> <li>• 67.5 MHz @ 1.70 dB</li> </ul> The attenuation applies to two devices connected to each other
Bandwidth	...	...	200 MHz
CMRR (dB @ 5MHz)	...	...	50 dB
Inputs protection	...	...	ESD, IEC 61000-4-2, $\pm 30$ kV contact, $\pm 30$ kV air EFT, IEC 61000-4-4, 40A (5/50ns) Lightning, IEC 61000-4-5, 30A ( $t_p=8/20\mu s$ )
Power supply	180 ... 240 V AC - Built-in switching power supply	...	—
Operation temp	...	...	-20 °C ... 55 °C

Weight	0.43 kg	4.72 kg	0.09 kg
Dimensions	158 x 118 x 77 mm	655 x 420 x (53 ... 464) mm	103 x 75 x 30 mm
Manufacturer / Brand	ATTE	BRATECK	DELTA
Guarantee	3 years	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00