



	WIRELESS VIDEO DOORBELL ATLO-DBC1-TUYA Wi-Fi, Tuya Smart	CEILING PIR DETECTOR AQUA-RING-S SATEL
		
	31.58 EUR 31.58 EUR	24.49 EUR 24.49 EUR
Application	...	Indoor
Pyroelectric sensor	...	Double
Sensor	Progressive Scan CMOS - 2 Mpx	...
Sensor type	...	Passive Infra Red (PIR)
Resolution	1920 x 1080 px - 1080p	...
Lens	2.5 mm	...
View angle	<ul style="list-style-type: none"> • 135 ° (manufacturer data) • 101 ° (our tests result) 	...
IR illuminator	10 m	...
Range	...	from a height 2.4 m area 36 m ² from a height 3.7 m area 80 m ²
LED illuminator	—	...
Sensitivity adjustment	...	By jumpers
Wireless transmission range	The range limited only by the availability of the Wi-Fi network	...
Recommended installation height	...	2.2 m ... 4.5 m
Wi-Fi standard	IEEE 802.11 b/g/n : 2.4 GHz	...
Autodiagnosics	...	Basic
Prealarm feature	...	✓
Network interface	Wi-Fi : 2.4 GHz	...
Pet immunity	...	—
Alarm time	...	2 s
Mobile phones support	The Tuya Smart free application on Android The Tuya Smart free application on iOS	...
Digital temperature compensation	...	✓
Image compression method	H.264 / MJPEG / JPEG	...
Main features	...	<ul style="list-style-type: none"> • Environmental immunity • Tamper protections • Power supply 24V AC/DC
Operation temp	...	-30 °C ... 55 °C

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Target speed range	...	0.3 ... 3 m/s
Manufacturer / Brand	...	SATEL
Main features	<ul style="list-style-type: none"> • Micro SD memory cards up to 128GB support (possible local recording), • PIR detector - Motion Detection, Detector range 3 m, • loitering detection • ICR - Movable InfraRed filter • Auto White Balance • AGC - Automatic Gain Control • BLC - Back Light Compensation, • Microphone built-in, • Speaker built-in, • Bidirectional communication, • Noise and echo reduction • Full support via network : WiFi, • Possibility to work in cloud - you don't need to redirect the ports, • Video PUSH personal messaging • Increased battery life • Low current consumption • Operating frequency - Wireless doorbell : 433 MHz 	...
Mount	Surface-mounted	...
Power supply	<ul style="list-style-type: none"> • 2 x 18650 battery 3.7 V / 2600 mAh (not included) • 5 V DC - Charging via micro USB port (cable included) 	<ul style="list-style-type: none"> • 24 V AC / 27 mA, • 24 V DC / 14 mA
Housing	Waterproof - Plastic	...
Color	White / Black	...
"Index of Protection"	IP66	...
Weight	<ul style="list-style-type: none"> • 0.084 kg - Wireless Video Doorbell • 0.028 kg - mounting base 	0.053 kg
Dimensions	<ul style="list-style-type: none"> • 142 x 46 x 32 mm - Wireless Video Doorbell • 158 x 62 x 17 mm - mounting base 	Ø 97 x 29 mm
Guarantee	2 years	2 years