





	<a href="#">HUB USB 3.0 F7U-U3-CR-BP 1 m</a>	<a href="#">EXTENDER VGA + USB CE-100</a>	<a href="#">HUB USB 3.0 HUB-USB3.0-1/4 55 cm</a>	<a href="#">CLEANER FOR RECOVERY OF POTENTIOMETERS KONTAKT-PR/400 SPRAY 400 ml AG TERMOPASTY</a>
				
	13.81 CHF 13.81 CHF	145.82 CHF 145.82 CHF	6.05 CHF 6.05 CHF	6.35 CHF 6.35 CHF
Package	...	...	...	Spray 400 ml
Application	...	...	...	Cleaning and regeneration of potentiometers
Connectors	<ul style="list-style-type: none"> <li>• 1 x Socket - micro USB 3.0</li> <li>• 7 x socket - USB-A</li> <li>• 1 x Power socket - micro USB</li> </ul>	...	<ul style="list-style-type: none"> <li>• 1 x socket - USB 3.0 Micro B</li> <li>• 4 x socket - USB 3.0 A</li> <li>• 1 x Power socket - 1.35 / 3.50 mm</li> </ul>	...
Length of the cable	1 m	...	55 cm	...
USB standard	3.0	...	3.0	...
Manufacturer / Brand	ORICO	...	...	AG TERMOPASTY
Device type	...	<b>Active / Transmitter</b> <b>Active / Receiver</b>	...	...
Number of channels	...	1 x VGA 2 x USB 1 x VGA 2 x USB	...	...
Power supply	5 V DC / 3 A (power adapter not included)	5 V / 1000 mA 5 V USB	...	...
Video transmission range	...	max. 100 m max. 100 m	...	...
Connectors type	...	1 x VGA Socket HDB-15 2 x USB-A Socket 1 x VGA Plug HDB-15 1 x USB-B Socket	...	...
Symmetrical socket type	...	RJ-45 (8-pin, 4 pairs) Socket RJ-45 (8-pin, 4 pairs) Socket	...	...
Weight	0.050 kg	0.170 kg 0.170 kg	0.044 kg	0.36 kg
Dimensions	135 x 35 x 19 mm	91 x 56 x 25 mm 91 x 56 x 25 mm	105 x 36 x 25 mm	Ø 66 x 187 mm
Main features	<ul style="list-style-type: none"> <li>• Solid workmanship</li> <li>• It can be used as a charger for multiple devices when connected to an external power source via the micro USB socket</li> <li>• LED indication</li> <li>• Transparent housing</li> </ul>	<ul style="list-style-type: none"> <li>• Real-time DDC communication support</li> <li>• Built-in ESD protection 8 / 15 kV</li> <li>• Manual compensation adjustment</li> <li>• Possibility to mount to the wall</li> </ul>	<ul style="list-style-type: none"> <li>• Solid workmanship</li> <li>• It can be used as a charger for multiple devices when connected to an external power source via the 3.50 / 1.35 mm socket</li> <li>• LED indication</li> <li>• The cable included in the kit: USB 3.0 A plug / USB 3.0 Micro B plug</li> <li>• Each socket has a separate switch</li> </ul>	Spray preparation with a brush for easy application in hard-to-reach places

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Resolution	...	<ul style="list-style-type: none"> <li>• 1920 x 1080 / 60 Hz @ 30 m</li> <li>• 1920 x 1200 / 60 Hz @ 30 m</li> <li>• 1280 x 1024 / 60 Hz @ 100 m</li> </ul>	...	...
Guarantee	2 years	2 years	2 years	...



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00