




	<a href="#">LABEL REMOVER ADHESIVE-REMOVER/200ML SPRAY 200 ml TESA</a>	<a href="#">MULTI-PURPOSE AGENT K2-07/500ML SPRAY 500 ml K2</a>	<a href="#">UNIVERSAL METER STC-23 DVB-T/T2 DVB-S/S2 DVB-C Spacetronek</a>
			
	7.88 EUR 7.88 EUR	5.02 EUR 5.02 EUR	110.27 EUR 110.27 EUR
Package	Spray 200 ml	Spray 500 ml	...
Output and input	...	...	1 pcs F socket, 1 pcs IEC socket, 1 pcs mini USB, 1 pcs 2.1/5.5 mm socket
Display	...	...	2.4 " TFT LCD
Application	Removal of self-adhesive labels	<ul style="list-style-type: none"> <li>• Elimination of squeaks,</li> <li>• Lubrication,</li> <li>• Removal of water,</li> <li>• Penetration,</li> <li>• Corrosion protection,</li> <li>• Surface preservation,</li> <li>• Removal of dirt</li> </ul>	...
Frequency range	...	...	<ul style="list-style-type: none"> <li>• 42 MHz ... 1005 MHz - DVB-T / DVB-T2 / DVB-C,</li> <li>• 950 MHz ... 2150 MHz - DVB-S / DVB-S2</li> </ul>
Signal level	...	...	-20 ... -80 dBm
LNB power supply	...	...	13 / 18 V
Switching between bandwidths	...	...	0 / 22 kHz
DiSEqC	...	...	DiSEqC 1.0, 1.1, 1.2, USALS systems support
Antenna powering	...	...	5 / 12 V
Video signal test	...	...	—
Programming and firmware upgrade	...	...	via micro USB port
Battery power supply	...	...	<ul style="list-style-type: none"> <li>• Li-Ion battery 7.4 V / 2000 mAh</li> <li>• 12 V / 1 A (power adapter included)</li> </ul>

Main features	...	<ul style="list-style-type: none"> <li>• Spray formulation with a straw for easy application in hard-to-reach places</li> <li>• Dual applicator - broad stream for application on a larger surface and precise stream (with a straw) for hard-to-reach places</li> <li>• It can be used in any position, even upside down</li> </ul>	<ul style="list-style-type: none"> <li>• Measurement of signal strength and quality</li> <li>• Signal indicator : LED display / Beep signal</li> <li>• Measurement of BER, MER</li> <li>• Spectrum measurement mode</li> <li>• LNB overvoltage protection</li> <li>• LNB indicator and short-circuit protection</li> <li>• Support for a satellite dish motor</li> <li>• UNICABLE technology support</li> <li>• Signal lock audible notification</li> <li>• Clear graphical interface</li> <li>• OSD menu full in Polish</li> <li>• Car charger included in the kit</li> <li>• Long standby time</li> <li>• Low power consumption</li> <li>• Compass</li> <li>• Flashlight built-in</li> <li>• Illuminated buttons</li> <li>• Anti-shock silicone case</li> </ul>
Weight	0.200 kg	0.43 kg	0.3 kg
Dimensions	Ø 53 x 173 mm	Ø 66 x 237 mm	170 x 93 x 42 mm
Supported languages	...	...	Polish, English, Spanish, Portuguese, Russian, French
Manufacturer / Brand	TESA	K2	Spacetrnik
Guarantee	...	...	2 years