



	SWITCH POE APTI-POE0402-60W 4-PORT	ACCESS CONTROLLER MODULE MC16-PAC-EX-2 ROGER
		
	36.92 EUR 36.92 EUR	517.39 EUR 517.39 EUR
Number of served transitions	...	2
Inputs	...	12
LAN ports	6 x RJ45 (4 x IEEE 802.3af)	...
Outputs	...	8
Number of users	...	max. 12000 - Number of identifiers
Number of media per ID	...	8 - Proximity card, PIN code, fingerprint, etc.
Number of permissions per ID	...	100
Management	—	...
Buffer memory	...	8 000 000 events buffer
MCT readers support	...	16 pcs
LED diodes	LAN, WAN, PoE	...
Readers connections	...	4 pcs - Wiegand / PRT
Number of login points	...	4
Number of access terminals	...	8
Number of access zones	...	4
Transmission speed	• 10 / 100 Mbps : 2 x Port LAN, • 10 / 100 Mbps : 4 x LAN & PoE ports	...
Number of alarm zones	...	4
Number of automation nodes	...	4
Maximal output power	15.4 W / port PoE	...
Maximal total power	60 W	...
Battery backup support	...	12 V / 7 Ah
MAC addresses table	2k	...
Communication	...	• Ethernet - RJ-45 socket • RS-485 interface • RACS 5 v2 (Roger)
Certificates	CE	...

Main features	<ul style="list-style-type: none"> • 2 x Port Uplink • Range PoE : 200 m - The EXTEND mode enabled 	<ul style="list-style-type: none"> • Integrated support in VISO EX software • Functions in the VISO EX system: - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system - unlimited - division of the system into partitions operated by independent operators - tool for integration with RACS5 (API) systems - integration with many systems (elevator systems, building applications, SMS, BMS, PSIM, VMS, Active Directory systems)
Power supply	230 V AC	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC
Operation temp	0 °C ... 55 °C	5 °C ... 40 °C
Permissible relative humidity	...	10 % ... 95 % (non-condensing)
Weight	0.65 kg	0.14 kg
Dimensions	220 x 141 x 41 mm	175 x 72 x 30 mm
Manufacturer / Brand	APTI	ROGER
Guarantee	2 years	3 years