






	ACCESS CONTROLLER WITH FACE RECOGNITION + READER ATLO-FR-601	RELAY MODULE AWZ-529	WIRELESS DOOR CHIME ATLO-DB-TUYA	MULTI-MODE MODULE XG: SFP-SR-MM850 SFP+ REYEE	SWITCH POE IPB-5-10A-S4 5-PORT ATTE
					
	552.78 SEK 552.78 SEK	69.44 SEK 69.44 SEK	67.42 SEK 67.42 SEK	1011.11 SEK 1011.11 SEK	900.53 SEK 900.53 SEK
Number of relay outputs	...	2
Signaling mode	Optical - sound signaling
Number of ring-tones	52
Transmission protocols	IEEE 10GBASE-SR, IEEE802.3ae	...
Face recognition distance	0,5 m ... 1 m (max 1000 faces in the database)
Current consumption	...	37 mA per each relay at voltage 12 V DC
Volume adjustment	4 volume levels, 10 ... 90 dB
Fiber type	50 / 125 µm / 62 / 125 µm Multi-mode fiber	...
RFID proximity reader built-in	Unique EM 125kHz - Number of supported proximity cards : 10 000
Operation range	80 m - in open area
Maximal transmission range	0.3 km	...
Fingerprint reader built-in	Memory of 600 fingerprint patterns
LAN ports	<ul style="list-style-type: none"> • 1 x RJ45 10/100 Base-T - Uplink • 5 x RJ45 10/100 Base-T - PoE (802.3af/at) / Passive PoE
Transfer rate	max. 10.3125 Gb/s	...
Range of IR illumination	5 m
Relay maximal load	...	2 A (max), 30 V DC / 50 V AC (max)
Frequency band	433.92 MHz ± 0.2
Number of used fibers	2	...
White light LED illuminator range	—
Output	...	2 x NO/NC
Optical connectors	2x LC / PC	...
Video output	—
Wiegand interface	✓
Management	—
Light source / optical wavelength	Surface VCSEL Laser / 850 nm	...
RS-485 interface	—
LED diodes	Power, LAN
Alarm inputs / outputs	0 / 1 - Relay output
Operation temp	...	-10 °C ... 40 °C	...	0 °C ... 70 °C	...
Transmission speed	10 / 100 Mbps ; 1 Port LAN + 5 LAN & PoE ports

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	<ul style="list-style-type: none"> • Built-in LCD display showing the image from the video camera • Identification modes : Face recognition, Fingerprint, Proximity identifier Unique EM 125kHz, Any combination of the above • Wiegand 26 • LEDs and buzzer • Buzzer for acoustic signaling of some system events
Power consumption	≤ 3.6 W (operation) ≤ 2.2 W (standby)	...	≤ 0.5 W
Maximal output power	<ul style="list-style-type: none"> • 40 W @ Passive PoE - 1 ... 5 ports, • 30 W @ PoE (802.3at) - 1 ... 5 ports • 15.4 W @ PoE (802.3af) - 1 ... 5 ports
Maximal total power	90 W
Housing	Aluminum + Tempered glass, Vandal-proof	...	Plastic
Color	Silver + Black	...	White
"Index of Protection"	IP65
Operation temp	-40 °C ... 60 °C
Main features	...	LED indication	<ul style="list-style-type: none"> • Low power consumption • Receiver sensitivity : -110 dBm • Simple and quick device installation 	...	<ul style="list-style-type: none"> • Supported PoE devices: 802.3af/at, Passive PoE • Possibility to connecting in cascade • Efficiency : 93 % @ 90 W • 5 polymer fuses - PoE • Possibility to power other devices powered from 55 V (screw connection) • PSU thermal protection • Short-circuit protection • Overload protection • The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 4 ports • Switch has built-in a 55 V DC power supply adapter with power of 90 W • "Index of Protection" : IP55
Power supply	12 V DC	10 ... 14 V DC	100 ... 240 V AC	3.3 V	180 ... 240 V AC - Built-in switching power supply
Weight	0.38 kg	0.04 kg	0.06 kg	0.02 kg	0.43 kg
Dimensions	170 x 70 x 24 mm	70 x 43 x 23 mm	82 x 82 x 65 mm	...	158 x 118 x 77 mm
Manufacturer / Brand	ATLO	PULSAR	...	RUIJIE / REYEE	ATTE
Guarantee	2 years	2 years	2 years	2 years	3 years