


	IP SPEED DOME CAMERA OUTDOOR IPC6424SR-X25-VF - 4 Mpx 4.8 ... 120 mm UNIVIEW
	
	1064.01 EUR 1064.01 EUR
Standard	TCP/IP
Sensor	1/2.8 " Progressive Scan CMOS
Matrix size	4 Mpx
Resolution	2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p
Lens	4.8 ... 120 mm
View angle	• 52 ° ... 2.7 ° (manufacturer data) • 52 ° ... 3.1 ° (our tests result)
Optical zoom	x 25
Digital zoom	x 16
Range of IR illumination	100 m
Video output	1 Vpp / 75 Ω - BNC plug
Preset rotation speed	• 240 °/s (horizontal) • 200 °/s (vertical)
Rotation speed (manual control)	• 0.1 °/s ... 200 °/s (horizontal), • 0.1 °/s ... 120 °/s (vertical)
Horizontal rotation range	360 ° - continuous
Vertical rotation range	-15 ° ... 90 °
RS-485 interface	✓
Number of presets	1024
Horizontal scan	—
Route settings	16
Image compression method	Ultra H.265 / H.265 / H.264 / MJPEG
Alarm inputs / outputs	2 / 1
Audio	• Audio input • Audio output • Bi-directional audio streaming support • Audio detection • Noise reduction
Main stream frame rate	1 ... 30 fps @ 4 Mpx
Network interface	10/100 Base-TX (RJ-45)
Network protocols	IPv4, IGMP, ICMP, ARP, TCP/IP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, IEEE 802.1x, SNMP, QoS, RTMP, SSL / TLS

WEB Server	Built-in
Max. number of on-line users	32
ONVIF	✓
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)
Mobile phones support	Access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EZView • iOS (iPhone): Free application EZView
Default IP address	DHCP or 192.168.1.13
Default admin user / password	admin / 123456
Web browser access ports	80, 554
PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation
Mobile client access ports	80
Port ONVIF	80
RTSP URL	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream
Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • F-DNR (Defog) - Reduction of image noise caused by precipitation • BLC/HLC - Back Light / High Light Compensation • Day/night mode • ICR - Movable InfraRed filter • Auto White Balance • Configurable Privacy Zones - 24 • Motion Detection • Tamper signaling • Image rotation and mirror • Adaptive adjusting of the IR illuminator power to the lens zoom and outdoor light conditions • Intelligent image analysis : crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area, Filtering of false alarms based on the recognition of persons and vehicles, face detection - supports 4 types of facial attributes extraction, counting people entering and leaving the area, crowd gathering estimation, Intelligent Object Tracking



Housing	Speed Dome, Metal + Plastic
Color	White + Black
"Index of Protection"	IP67
Vandal-proof	IK10
Power supply	<ul style="list-style-type: none"> • PoE (802.3at), • 12 V DC / 3 A (power adapter included)
Power consumption	≤ 21 W
Operation temp	-40 °C ... 70 °C
Weight	3.35 kg
Dimensions	Ø 166 x 295 mm (without bracket)
Supported languages	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Slovenian, Hungarian, Italian
Manufacturer / Brand	UNIVIEW
Guarantee	2 years