

	NVR APTI-N3212AI-32 CHANNELS	POWER DISTRIBUTION UNIT PD-6/R-2P 1.8 m	NVR APTI-N2522-4KS5 25 CHANNELS	TWILIGHT SWITCH FOR LED LIGHTING TWILIGHT-SWITCH/BLEBOX 12 ... 24 V DC
				
	339.33 AUD 339.33 AUD	36.47 AUD 36.47 AUD	160.09 AUD 160.09 AUD	13.81 AUD 13.81 AUD
Standard	TCP/IP	...	TCP/IP	...
Supported resolutions	max. 12 Mpx - 4000 x 3000 px	...	max. 8.3 Mpx 4K UHD - 3840 x 2160 px	...
Application	Works with LED lighting - 12-24V LED strips
Video outputs	1 pcs HDMI 4K 1 pcs VGA	...	1 pcs HDMI 1 pcs VGA	...
Rated voltage	...	230 V AC / 50 Hz	...	12 ... 24 V DC
Number of outlets	...	6 x CEE 7/5
Maximal total load	...	3680 W	...	60 ... 120 W
Assembly	...	In RACK 19" cabinets
Total maximal current	...	16 A	...	5 A
Number of inputs	0
Length of the power cable	...	1.8 m, cable with power connector CEE 7/7
Audio support	<ul style="list-style-type: none"> • 32 Channels - Audio from cameras, • Bi-directional audio streaming support • Compliance with the AAC standard 	...	25 Channels - Audio from cameras	...
Number of outputs	1
Housing type	...	1 U RACK 19"
Audio inputs	1 pcs CINCH	...	1 pcs Cinch socket	...
Audio outputs	1 pcs CINCH	...	1 pcs Cinch socket	...
Connector type	PCB (soldering)
Wireless	—
Image compression method	H.265+ / H.265 / H.264+ / H.264	...	H.265+ / H.265 / H.264+ / H.264	...
Supported hard drives	2 x 10 TB SATA	...	2 x 8 TB SATA	...
Recording modes	Manual, Sensor, Motion detection, Schedule	...	Manual, Motion Detection, Schedule	...
Network interface	1 x RJ-45 10/100/1000 Base-TX
Main features	...	Circuit Breaker, 16 A, C type, 2P	...	<ul style="list-style-type: none"> • High power - max. 120 W, • Automatic calibration, • Mild lightening at dusk, • Mild darkening at dawn, • Small dimensions, • Possible assembly in a profile
Housing	—

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

"Index of Protection"	—
Color	—
External storage devices backup	Records backup at (.avi) format to USB (pendrive)	...	Records backup at (.avi) format to USB (pendrive)	...
Network protocols	IPv6, TCP/IP, HTTP, HTTPS, UPnP, DNS, NTP, SMTP, DHCP, FTP, DDNS, RTSP, RTCP, P2P, PPPoE	...	TCP/IP, HTTP, HTTPS, UPnP, DNS, NTP, SMTP, DHCP, FTP, DDNS, RTSP, RTCP, P2P, PPPoE, ONVIF	...
Searching and playback the records	Records searching: timeline or file list. Playback: forward, fast Playback max. 16 cameras in the same time @ 1080p	...	Records searching: timeline or file list. Playback: forward, fast Simultaneous playback : • 1 Channel @ 8 Mpx • 1 Channel @ 5 Mpx • 2 Channels @ 4 Mpx • 2 Channels @ 3 Mpx • 4 Channels @ 1080p • 4 Channels @ 960p • 4 Channels @ 720p	...
Bitrate	320 Mbps	...	100 Mbps	...
Network functions	Network Client Software and IE browser: live view, playback and backup of the records, configuration of the recorder parameters	...	Network Client Software and IE browser: live view, playback and backup of the records, configuration of the recorder parameters	...
ONVIF	✓	...	✓	...
Mobile phones support	Access by a cloud (P2P) • Android: Free application BitVision , Android: Free application iVMS320 • Android: Free application BitVision , iOS: Free application iVMS320	...	Port no.: 6000 or access by a cloud (P2P) • Android: Free application BitVision , Android: Free application iVMS320 • iOS (iPhone): Free application BitVision , iOS: Free application iVMS320	—
USB	• 1 pcs USB 2.0 • 1 pcs USB 3.0	...	2 pcs USB 2.0	...
Default IP address	192.168.1.88	...	192.168.1.88	...
Serial ports	—
Default admin user / password	admin / 12345	...	admin / 12345	...
Web browser access ports	80, 5000, 554	...	80, 5000, 554	...
PC client access ports	80, 5000, 554	...	80, 5000, 554	...
Mobile client access ports	80, 5000, 554	...
Alarm inputs / outputs	4 / 1	...	8 / 4	...
Intelligent image analysis	✓
PTZ control	IP Speed Dome Cameras	...	IP Speed Dome Cameras	...
Main features	• Support for intelligent image analysis, available in cameras from the APTI-AI series • D-ZOOM - Digital Zoom
Motion Detection	Split the screen into zones : 22 x 18 motion zones	...	Split the screen into zones : 24 x 18 motion zones	...
Mouse support	✓	...	✓	...

IR remote controller in the set	—	...	—	...
Power supply	12 V / 4 A (power adapter included)	...	12 V DC / 4 A	...
Power consumption	≤ 15 W (without HDD)
Operation temp	-10 °C ... 50 °C	...	-10 °C ... 55 °C	-20 °C ... 50 °C
Weight	2.71 kg	0.91 kg	1.31 kg	0.001 kg
Dimensions	380 x 323 x 51 mm	483 x 45 x 85 mm	310 x 305 x 46 mm	34 x 8.5 x 4 mm
Supported languages	Polish, English, French, Spanish, German, Portuguese, Russian, Ukrainian, Italian	...	Polish, English, Bulgarian, Czech, French, Greek, Spanish, German, Portuguese, Russian, Turkish, Hungarian, Italian	...
Manufacturer / Brand	APTI	...	APTI	BleBox
Guarantee	2 years	2 years	2 years	2 years

