






	<a href="#">COAXIAL CABLE TRI-LAN-400.50 Ω</a>	<a href="#">WORK GLOVES WG-422/L Bee-Smart WONDER GRIP</a>	<a href="#">RUBBER MAT MB-GUM/50</a>	<a href="#">MONITORS DESK MOUNT MC-691 MACLEAN</a>	<a href="#">EXTENSION CORD WITH GROUNDING PS-3X1.0-1.5M/W 1.5 m</a>
					
	2.81 EUR 2.81 EUR	5.54 EUR 5.54 EUR	6.31 EUR 6.31 EUR	61.05 EUR 61.05 EUR	4.71 EUR 4.71 EUR
Length of the cable	...	...	...	...	1.5 m
Wire gauge	...	...	...	...	3 x 1 mm <sup>2</sup>
Mounting standard	...	...	...	VESA 75, VESA 100	...
Rated voltage	...	...	...	...	230 V AC / 50 Hz
In section	<b>100 m . Price for 1m when buying a whole roll</b>	...	...	...	...
Screen size range	...	...	...	13 " ... 27 "	...
Total maximal current	...	...	...	...	10 A
Bearing capacity	...	...	...	8 kg	...
Maximal total load	...	...	...	...	2300 W
Number of outlets	...	...	...	...	1 x CEE 7/5
Inner conductor	Ø 2.7 mm Cu ± 0.02 mm Wire	...	...	...	...
Application	...	<ul style="list-style-type: none"> <li>• Construction and public works,</li> <li>• Warehousing - packing and logistics,</li> <li>• DIY,</li> <li>• Assembly</li> </ul>	<ul style="list-style-type: none"> <li>• Area covering,</li> <li>• Soundproofing</li> </ul>	...	...
Fuse	...	...	...	...	—
Tilt adjustment	...	...	...	-45 ° ... 45 °	...
Switch	...	...	...	...	—
Dielectric	Ø 7.2 mm Physical foam	...	...	...	...
Horizontal rotation	...	...	...	180 °	...
Color	...	Black + Blue	Black	Black	White
Rotation in the plane of the screen	...	...	...	360 °	...
Shield	Foil - Al/PET	...	...	...	...
Mount tube diameter	...	...	...	Ø 35 mm	...
Material	...	Polyester + latex coating (palm coated)	SBR granulate + polyurethane binder	...	...
Braid	168 x Ø 0.15 mm Stranded wire CuSn	...	...	...	...
Weight	...	...	2.4 kg	6 kg	0.17 kg
Impedance	50 Ω	...	...	...	...
Outer coating	Ø 10.3 mm ± 0.20 mm PE	...	...	...	...
Dimensions	...	...	500 x 500 x 10 mm	1330 x 550 x 83 mm	...
Supported norms	...	<ul style="list-style-type: none"> <li>• EN 388:2016 - Mechanical protection 3131X</li> <li>• EN 407:2004 - Thermal protection X1XXXX</li> </ul>	...	...	...
Main features	<ul style="list-style-type: none"> <li>• low attenuation</li> <li>• perfect matched</li> <li>• high screening efficiency</li> <li>• it can be used in WLAN 2,4GHz and 5GHz installations</li> <li>• Operation temp : -40 °C ... 70 °C</li> </ul>	<ul style="list-style-type: none"> <li>• Thermal protection : 100 °C ( X1XXXX ),</li> <li>• Ergonomics and comfort</li> <li>• High grip</li> <li>• Soft coating</li> </ul>	<ul style="list-style-type: none"> <li>• Rough structure</li> <li>• Granule fraction : 0.5 ... 4 mm</li> <li>• Insulation</li> <li>• High fatigue strength of the material</li> <li>• Weatherproof</li> <li>• Very easy and quick assembly</li> </ul>	...	...
Size	...	9 / L	...	...	...
Manufacturer / Brand	...	WONDER GRIP	...	MACLEAN	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Cable attenuation at 100m section	Temperature : 20 °C				
	2.3 dB @ 30 MHz 3.0 dB @ 50 MHz 4.9 dB @ 150 MHz 6.0 dB @ 220 MHz 8.7 dB @ 450 MHz 12.8 dB @ 900 MHz 17.0 dB @ 1500 MHz 18.8 dB @ 1800 MHz 20.0 dB @ 2000 MHz 22.7 dB @ 2500 MHz 37.6 dB @ 5800 MHz	...	...	...	...
Maximum transmitted power	3.36 kW @ 30 MHz 2.59 kW @ 50 MHz 1.47 kW @ 150 MHz 1.20 kW @ 220 MHz 0.82 kW @ 450 MHz 0.57 kW @ 900 MHz 0.43 kW @ 1500 MHz 0.39 kW @ 1800 MHz 0.36 kW @ 2000 MHz 0.32 kW @ 2500 MHz 0.20 kW @ 5800 MHz	...	...	...	...
Guarantee	2 years	...	...	2 years	2 years

