



	IP CAMERA DS-2CD2026G2-IU/SL(2.8MM) ACUSENSE - 1080p Hikvision	GRAPHITE VARNISH GRAPHITE-VARNISH 2 X VIAL 1.5 ml AG TERMOPASTY
		
	261.75 EUR 261.75 EUR	2.87 EUR 2.87 EUR
Standard	IP	...
Package	...	2 x Vial 1.5 ml (varnish + solvent)
Application	...	<ul style="list-style-type: none"> • Repair and renovation of graphite coatings in electronic devices, • Reconstruction of paths in printed circuit boards
Resolution	1920 x 1080 - 1080p , 1280 x 720 - 720p	...
Sensor	1/2.8 " Progressive Scan CMOS	...
Lens	2.8 mm	...
View angle	107 °	...
Compression	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Main features	...	<ul style="list-style-type: none"> • Density : 1.2 g/cm³ @ 20 °C, • Viscosity : 15 ... 50 Pa·s @ 20 °C • Good electrochemical corrosion protection on metal • Photosensitive varnish • Dedicated solvent (ethyl acetate) included
Range of IR illumination	40 m	...
Audio	<ul style="list-style-type: none"> • Microphone built-in, • Speaker built-in - Alarm siren 	...
Alarm inputs / outputs	—	...
Memory card slot	Micro SD card support up to 256GB	...
Main stream frame rate	25 fps @ 4 Mpx	...
Network interface	10/100 Base-T (RJ-45)	...
WEB Server	Built-in	...
Max. number of on-line users	6	...
ONVIF	✓	...
Mobile phones support	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application Hik-Connect • iOS: Free application Hik-Connect 	...
Default IP address	192.168.1.64	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80	...
PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	...
Mobile client access ports	8000	...
Port ONVIF	80	...
RTSP URL	<ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ 	...
Intelligent image analysis	<ul style="list-style-type: none"> • crossing the line (tripwire) • intrusion • detection of entry into the area / exit from the area • classification of people and vehicles • scene changing • face detection 	...
Main features	<ul style="list-style-type: none"> • Active deterrence function - Light and sound alarm • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ROI - improve the quality of selected parts of image • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network • Anti-Flicker - The technology eliminates the tiring eyes flickering image effect • Day/night mode • ICR - Movable InfraRed filter • Auto White Balance • AGC - Automatic Gain Control • Possibility to change the resolution, quality and bit rate • Sharpness - sharper image outlines • Mirror - Mirror image • Configurable Privacy Zones • Motion Detection • Filtering of false alarms based on the recognition of persons and vehicles 	...
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 540 mA 	...
Power consumption	<ul style="list-style-type: none"> • ≤ 8 W @ PoE (802.3af) • ≤ 6.5 W @ 12 V DC 	...
Housing	Compact, Metal	...
Color	White	Black
"Index of Protection"	IP67	...
Operation temp	-30 °C ... 60 °C	...

Supported languages	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Vietnamese, Italian	...
Weight	0.59 kg	...
Dimensions	Ø 74 x 191 mm	...
Manufacturer / Brand	Hikvision	AG TERMOPASTY
SAP Code	311312612	...
Guarantee	3 years	...



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00