





	<a href="#">EXTENDER VGA-EX-30</a>	<a href="#">IP SPEED DOME CAMERA INDOOR SD29404DB-GNY WizSense - 3.7 Mpx 2.8 ... 12 mm DAHUA</a>	<a href="#">SILICON OIL SILICONE OIL/300 SPRAY 300 ml AG TERMOPASTY</a>	<a href="#">TV OR MONITOR MOUNT BRATECK-LP77-44T</a>
				
	42.31 EUR 42.31 EUR	531.74 EUR 531.74 EUR	5.56 EUR 5.56 EUR	11.99 EUR 11.99 EUR
Standard	...	IP	...	...
Device type	Passive	...	...	...
Package	...	...	Spray 300 ml	...
Video transmission range	max. 180 m	...	...	...
Symmetrical socket impedance	100 Ω	...	...	...
Application	...	...	Lubrication, Pulling wires, Elimination of corona discharges and eddy-currents, Protection against moisture ingress, Extrusion and vacuum forming of plastics	...
Main features	...	...	Spray formulation with a straw for easy application in hard-to-reach places	...
Connectors type	• 1 x VGA - Socket • 1 x RJ-45 - Socket	...	...	...
Mounting standard	...	...	...	VESA 100, 150, 200, 200x100, 300, 300x200, 400x200 400x300, 400
Screen size range	...	...	...	32 " ... 70 "
Bearing capacity	...	...	...	75 kg
Distance from mounting surface	...	...	...	47 mm
Sensor	...	1/2.8 " Progressive Scan CMOS	...	...
Tilt adjustment	...	...	...	-10 ° ... 4 °
Lens	...	2.8 ... 12 mm	...	...
View angle	...	95 ° ... 30 °	...	...
Optical zoom	...	x 4	...	...
Digital zoom	...	x 16	...	...
Range of IR illumination	...	50 m	...	...
Video output	...	—	...	...
Rotation speed (manual control)	...	• 0.1 °/s ... 100 °/s (horizontal), • 0.1 °/s ... 60 °/s (vertical)	...	...
Preset rotation speed	...	• 100 °/s (horizontal) • 60 °/s (vertical)	...	...
Horizontal rotation range	...	0 ° ... 360 ° - Rotation of the head is limited by stops	...	...
Vertical rotation range	...	0 ° ... 90 °	...	...
RS-485	...	—	...	...
Number of presets	...	300	...	...
Horizontal scan	...	✓	...	...
Route settings	...	5	...	...
Resolution	• 1920 x 1200 px WUXGA @ 45 m (manufacturer data) @ 30 m (our tests result), • 1600 x 1200 px UXGA @ 45 m (manufacturer data) @ 30 m (our tests result), • 1280 x 1024 px SXGA @ 60 m (manufacturer data) @ 40 m (our tests result), • 1280 x 768 px WXGA @ 60 m (manufacturer data) @ 40 m (our tests result), • 1024 x 768 px XGA @ 75 m (manufacturer data) @ 50 m (our tests result), • 800 x 600 px SVGA @ 120 m (manufacturer data) @ 80 m (our tests result), • 640 x 480 px VGA @ 180 m (manufacturer data) @ 120 m (our tests result)	2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p	...	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Bandwidth	≤ 60 MHz DC	...	...	...
Insertion loss	< 3 dB	...	...	...
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...	...
Grounding	via grounding bolt	...	...	...
Alarm inputs / outputs	...	2 / 1	...	...
Operation temp	0 °C ... 55 °C	...	...	...
Main stream frame rate	...	25 fps - 3.7 Mpx	...	...
Permissible relative humidity	≤ 95 %	...	...	...
Memory card slot	...	Micro SD card support up to 256GB	...	...
Network interface	...	10/100 Base-T (RJ-45)	...	...
WEB Server	...	Built-in, NVR compliance	...	...
Max. number of on-line users	...	20	...	...
ONVIF	...	✓	...	...
Audio	...	<ul style="list-style-type: none"> <li>• Microphone built-in,</li> <li>• External microphone input</li> <li>• Audio output</li> <li>• Audio transmission via network</li> <li>• Bi-directional audio streaming support</li> </ul>	...	...
Mobile phones support	...	Port 37777 <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">DMSS</a></li> <li>• iOS (iPhone): Free application <a href="#">DMSS</a></li> </ul>	...	...
Default admin user / password	...	admin / - The administrator password should be set at the first start	...	...
Default IP address	...	192.168.1.108	...	...
Web browser access ports	...	80, 37777	...	...
PC client access ports	...	37777	...	...
Mobile client access ports	...	37777	...	...
Port ONVIF	...	80	...	...
RTSP URL	...	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...	...
Intelligent image analysis	...	<ul style="list-style-type: none"> <li>• intrusion</li> <li>• crossing the line (tripwire)</li> <li>• detection of crossing a virtual fence</li> <li>• abandoned/missing object</li> <li>• fast moving</li> <li>• detection of people gathering</li> <li>• face detection - advanced face capture features</li> </ul>	...	...
Main features	...	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 2D-DNR, 3D-DNR - Digital Noise Reduction</li> <li>• EIS - Electronic Image Stabilization</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• SMD 3.0 - searching for an object classified as: human, motor vehicle</li> <li>• Day/night mode</li> <li>• BLC - Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• Configurable Privacy Zones</li> <li>•</li> <li>• Intelligent 3D Positioning System</li> </ul>	...	...
Power supply	---	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 830 mA</li> </ul>	...	...
Power consumption	...	≤ 10 W	...	...
Housing	...	Speed Dome, Plastic	...	...
Color	...	White + Black	...	Black
"Index of Protection"	...	---	...	...
Operation temp	...	-30 °C ... 50 °C	...	...
Weight	0.06 kg	0.7 kg	0.28 kg	2 kg
Dimensions	64 x 61 x 25 mm	Ø 132 x 117 mm	Ø 53 x 237 mm	570 x 430 x 47 mm
Supported languages	...	Polish, English	...	...
Manufacturer / Brand	...	DAHUA	AG TERMOPASTY	...
Guarantee	2 years	3 years	...	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00