

	HUB USB 3.0 C7P4U3-13AB- EU-WH-BP 1 m	LITHIUM BATTERY, BAT- CR2025*P2 ENERGIZER	VIDEO DOORPHONE VT06210RW DAHUA	ROUTER WIFI LR300 2.4 GHz 300 Mbps INOUI	UPS COVER WINTER-3K 3000 VA COVER	UPS AT UPS3000R-RACK 3000 VA EAST	IP CAMERA APTLAI60R21W-36AD Active Deterrence - 5 Mpx 3.6 mm	ACCESS POINT AC 11E +ROUTER ARCHER-MR400 2.4 GHz 5 GHz 867 Mbps + 300 Mbps TP-LINK	CONVERTER MODULE PZLXL16019 DC/DC
									
	36.90 EUR 36.90 EUR	1.57 EUR 1.57 EUR	195.52 EUR 195.52 EUR	11.53 EUR 11.53 EUR	497.24 EUR 497.24 EUR	450.88 EUR 450.88 EUR	79.57 EUR 79.57 EUR	125.86 EUR 125.86 EUR	2.09 EUR 2.09 EUR
Standard	IP
Power adapter type	Line-interactive	Line-interactive
Nominal power	2700 W	2400 W
Apparent Power	3000 VA	3000 VA
Frequency range	2.4 GHz	2.4 GHz , 5 GHz ,	...
LED illuminator	✓
Type	Increasing the voltage, DC/DC , Impulse regulator
In package	...	2 pcs The price for package
Compatibility	DAHUA
Rated voltage	...	3 V
Connectors	• 1 x Socket - USB-B 3.0 • 13 x socket - USB-A • 1 x Power socket - 5.5/2.1 socket
Power voltage	3 ... 35 V DC
Type (size)	...	CR2025
Length of the cable	1 m
proximity reader built-in	Access control cards - 13.56 MHz S50
Input voltage	162 V ... 290 V AC	• 70 ... 150 V AC • 145 ... 300 V AC
USB standard	3.0
UTP category	UTP cat. 5e
Antenna type	2 x Omnidirectional antenna - Integrated	3 x WiFi - built-in , 2 x 4G LTE	...
Output voltage adjustment	Precision potentiometer adjustment
Input frequency	50 / 60 Hz	50 / 60 Hz (auto detection)
Output current	5 A (max)
Standards	IEEE 802.11 a/b/g/n	IEEE 802.11 b/g/n, IEEE 802.11 a/n/ac, IEEE 802.3/3u	...
LED indicators	Status
Resolution	2592 x 1944 - 5 Mpx , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
DHCP server	✓
Power factor	0.9
Sensor	1/4 " , 1.0 Mpx CMOS	1/2.8 " SONY Starvis™ Back-illuminated CMOS
Firmware update	✓
Lens	3.6 mm
View angle	80°
Management interface	Web browser
Range of IR illumination	25 m
Transmitter power	max. 20 dBm
White light LED illuminator range	25 m
Memory card slot	Micro SD memory cards up to 1TB support (possible local recording)
Charging time (recover to 90% capacity)	8 hours
Output voltage	208 V / 220 V / 230 V / 240 V AC (Pure Sine Wave)	• 100 / 110 / 115 / 120 V AC ± 5 % (Pure Sine Wave) • 200 / 220 / 230 / 240 V AC ± 5 % (Pure Sine Wave)	5 ... 40 V DC
Baud rates	300 Mbps	• 5 GHz : 867 Mbps (max) + 2.4 GHz : 300 Mbps (max) • LTE : 150 Mbps	...
Image compression method	H.264	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Output frequency	50 / 60 Hz (auto detection) ± 1 Hz	50 / 60 Hz ± 0.3 Hz
Alarm inputs / outputs	1 / 1
Voltage adjustment	✓
Frequency adjustment	✓
Transfer time	max. 6 ms	≤ 10 ms
Modulation type	DBPSK, DQPSK, CCK OFDM, 16-QAM, 64-QAM	...
Battery	6 pcs	4 x 12V/9Ah
Estimated battery operation time	• 12 minutes @ 1350 W, • 7 minutes @ 2025 W, • 4 minutes @ 2700 W
Audio	• Microphone built-in, • Speaker built-in, • Bi-directional audio streaming support, • Audio transmission via network
Main stream frame rate	max. 25 fps @ 5 Mpx
LAN ports	3 x 10/100 Mbps LAN 1 x 10/100 Mbps WAN	• 1 x 10/100 Mbps - LAN/WAN • 3 x 10/100 Mbps - LAN	...
Number of outputs	8 pcs IEC-320 C13 + 1 pcs IEC-320 C19	6 pcs IEC320 C13
Interface	10/100 Base-T (RJ-45)
Management software	ViewPower
WEB Server	Built-in
Max. number of on-line users	10
ONVIF	19.12

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Protections				WPA-PSK, WPA2-PSK	<ul style="list-style-type: none"> Short-circuit Overload Overcharge protection discharge protection Output voltage filtering EPO (Emergency power off) switch 	<ul style="list-style-type: none"> Fuse Overload Short-circuit Discharge Overcharge Temperature Ethernet filter 		
Additional protection						RJ45		
Intelligent image analysis							<ul style="list-style-type: none"> intrusion - classification of people and vehicles crossing the line (tripwire) - classification of people and vehicles detection of people gathering loitering detection motion detection based on human detection 	
Receiver sensitivity							5 GHz : <ul style="list-style-type: none"> 11a 54M: -74dBm 11ac HT20: -67dBm 11ac HT40: -64dBm 11ac HT80: -60dBm 11n HT20: -71dBm 11n HT40: -70dBm 2.4 GHz : <ul style="list-style-type: none"> 11g 54M: -76dBm 11n HT20: -73dBm 11n HT40: -67dBm 	
LTE								✓
QSS								✓
WDS								✓
Number of LAN ports								4 x 10/100 Mbps
Operation temp			30 °C ... 60 °C		-10 °C ... 40 °C			0 °C ... 40 °C
Permissible relative humidity					10 % ... 90 % (non-condensing)			95 % (non-condensing)
Operation state indication					<ul style="list-style-type: none"> LCD display: operation mode, battery charging level, in/out voltage level, Sound signaling 	<ul style="list-style-type: none"> Large, readable LCD display with backlight : Voltage, Current frequency, Work load, Battery charge level, Temperature, Fan status, LED indicators displaying the device's operating status : Operation modes - On-Line / Battery / Bypass, Error, Sound signaling 		
Main features							<ul style="list-style-type: none"> Active intrusion deterrence works by blinking blue and red light and siren sound or voice prompts WDR - Wide Dynamic Range 3D-DNR - Digital Noise Reduction F-DNR (Defog) - Reduction of image noise caused by precipitation ROI - improve the quality of selected parts of image Flicker Control - The technology eliminates the tiring eyes flickering image effect BLC - Back Light Compensation HLC - High Light Compensation (spot) ICR - Movable InfraRed filter Smart motion detection (with recognizing people and vehicles) Privacy zones - max. 3 Image rotation and mirror Day/Night mode - configurable Sharpness - sharper image outlines 	
Mobile phones support			Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> Android: Free application DMSS iOS (iPhone): Free application DMSS There are also other versions of mobile applications: gDMSS Plus, iDMSS Plus				Port no.: 80 or access by a cloud (P2P) <ul style="list-style-type: none"> Android: Free application BitVision iOS (iPhone): Free application BitVision 	
Default IP address								192.168.1.168
Default admin user / password								admin / admin
Web browser access ports								80
PC client access ports								80
Mobile client access ports								80
Port ONVIF								80
Main features	<ul style="list-style-type: none"> Solid workmanship LED indication Each socket has a separate switch 		<ul style="list-style-type: none"> Doorbell button, Bidirectional communication, Microphone built-in, Speakers built-in, Tamper detection - removing from mounting surface 	<ul style="list-style-type: none"> Static / dynamic routing Built-in 3-port switch DMZ UPnP DHCP client list 	<ul style="list-style-type: none"> Auto restart while AC is recovering Automatic bypass The device has a rotating display COLD START function for manual switch to the battery power supply Battery charge and maintenance control COLD START function for manual switch to the battery power supply Remote management - ViewPower application (included) Battery replacement during operation (Hot-swap) Network card slot Can be mounted in a Rack 19" cabinet 	<ul style="list-style-type: none"> Auto restart while AC is recovering Automatic Voltage Regulator (AVR) "Cold Start" function Remote management Excellent microprocessor control guarantees high reliability UPS auto diagnostic system Battery charge and maintenance control Automatic battery charging in OFF mode Port USB - Access from PC SNMP - Option Power-saving mode (selectable in the menu) 	<ul style="list-style-type: none"> SIM socket WPS/RESET button 	
RTSP URL								rtsp://user:password@ip_address:80/0 Main stream rtsp://user:password@ip_address:80/1 Sub stream
Application					<ul style="list-style-type: none"> Surveillance Systems data storage centers network, servers, workstations Industrial Equipment 	<ul style="list-style-type: none"> Surveillance Systems data storage centers network, servers, workstations Industrial Equipment 		
Power supply	12 V DC / 5 A (included)		<ul style="list-style-type: none"> 12 V DC / 830 mA, 24 V PoE - DAHUA 	12 V DC / 0.5 A (power adapter included)				<ul style="list-style-type: none"> PoE (802.3af), 12 V DC / 400 mA
Housing type					Rack/Tower 2-in-1 Design	Rack/Tower 2-in-1 Design		
Power consumption					≤ 3.2 W			≤ 4.8 W



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Housing	Plastic	...	Plastic / Tempered glass, Waterproof	Compact, Metal
Operation temp. / Relative humidity	0 °C ... 40 °C / 0 ~ 95 % (non-condensing)	5 °C ... 40 °C ≤ 93 % (non-condensing)
Color	White + Silver	White
"Index of Protection"	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone	IP67
Mechanical protection class	---
Operation temp	-30 °C ... 60 °C
Weight	0.191 kg	0.002 kg	0.37 kg	0.13 kg	29.2 kg	26.2 kg	0.55 kg	0.26 kg	0.016 kg
Dimensions	235 x 62 x 28 mm	Ø 20 x 2.5 mm	154 x 114 x 43 mm	152 x 150 x 125 mm	438 x 630 x 88 mm ; RACK 19", 2U	440 x 133 x 405 mm ; RACK 19", 3U	Ø 73 x 175 mm	202 x 163 x 34 mm	49 x 28 x 14 mm
Supported languages	English, Bulgarian, Czech, Finnish, Polish, Slovenian, Slovak, Hungarian	Polish, English, French, Russian, Spanish, Portuguese, Italian, Ukrainian, Hungarian
Manufacturer / Brand	ORICO	ENERGIZER	DAHUA	IMOU	COVER	EAST	APTI	TP-LINK	...
Guarantee	2 years	2 years	3 years	2 years	2 years	2 years	2 years	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00