







	CONNECTOR WITH ELASTIC SEALING F/6.8-C*P100	EXTENDER HDMI+USB-EX-100-4K	EXTENDER TRANSMITTER HDMI-EX-150IR/TX-V4	TV OR MONITOR MOUNT BRATECK-LCD-142A	TV OR MONITOR MOUNT BRATECK-LPA78-446	FOOTING FOR MASTS MK-1.5/POD-HD
						
	14.09 GBP 14.09 GBP	172.87 GBP 172.87 GBP	68.30 GBP 68.30 GBP	13.48 GBP 13.48 GBP	10.33 GBP 10.33 GBP	154.50 GBP 154.50 GBP
Device type	Transmitter
HDMI standard	1.3
HDCP	1.4
Protocols	HDbiT
In package	100 pcs The price for package
Connector type	"F" Straight plug
Attachment of connector elements	Twisted-on
Shield fastening	Twisting-on
Wire mounting	—
Application	Coaxial cable
Cable diameter	max. 6.8 mm
Supported HDMI resolutions	...	480p, 576i, 576p, 720p 1080i, 1080p, 4K x 2K, 4K UHD	1080p, 1080i, 720p, 576p, 576i, 480p, 480i
Mounting standard	VESA 75, 100, 150, 200, 200x100	VESA : 75, 100, 100x150, 150x150, 200x100, 200, 300x200, 300, 400x200, 400x300, 400	...
Impedance	75 Ω
Material	Metal	Steel - Hot-dip galvanized
Screen size range	17 " ... 37 "	37 " ... 70 "	...
Example of application	RG6
Bearing capacity	20 kg	40 kg	...
Distance from mounting surface	70 ... 250 mm from wall	67 ... 355 mm	...
Main features	...	• Extender also allows to extend an USB 2.0 port, eg. in order to control the recorder using the mouse
Color	Black	Black	...
Tilt adjustment	-15 ° ... 15 °	-15 ° ... 3 °	...
Maximal transmission range	...	• 70 m UTP cat. 6 @ 4K UHD, • 70 m UTP cat. 5, 5e @ 1080p • 50 m UTP cat. 5e @ 4K UHD (our tests result)	• 120 m @ 1080p - UTP cat. 6 • 100 m @ 1080p - UTP cat. 5e • 80 m @ 1080p - UTP cat. 5
Horizontal rotation	Articulated arm with two swivels in range -90 ° ... 90 ° each	-60 ° ... 60 °	...
Rotation in the plane of the screen	360 °	-3 ° ... 3 °	...
Manufacturer / Brand	BRATECK	DELTA
Permissible relative humidity	...	0 % ... 90 % (non-condensing)
Main features	• Wide frequency range • Corrosion resistance • Elastic sealing	• Very good image quality with no visible distortions caused by compression • No delays in video transmission • No delays in mouse control operations • Transition of the HDMI signal in the transmitter • S/PDIF output	• IR carrier frequency : 20 ... 60 kHz • Baudrate : 18 Mbps • Protections : lightning, Overvoltage, ESD	• The design allows the mast to tilt up to 90° from the vertical, • Plate thickness : 10 mm, • Reinforced hinges
Power supply	...	• Transmitter 5 V DC / 2 A (power adapter included) • Receiver 5 V / 2 A (power adapter included)	5 V DC / 1 A - (power adapter included)
Current consumption	3 W
Operation temp	...	-20 °C ... 60 °C	0 °C ... 60 °C
Weight	0.005 kg	0.29 kg	0.146 kg	1.1 kg	3.36 kg	7.27 kg

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Dimensions	Ø 11 mm x 20 mm	150 x 107 x 28 mm - Transmitter or receiver dimensions	97 x 94 x 24 mm	195 x 119 x (70 ... 250) mm	440 x 420 x (67 ... 355) mm	395 x 350 x 107 mm
Guarantee	2 years	2 years	2 years	2 years	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00