



	ACCESS CONTROLLER DS-K2602T Hikvision	ACCESS CONTROLLER MODULE MC16-PAC-EX-2 ROGER
		
	15138.46 CZK 15138.46 CZK	13107.69 CZK 13107.69 CZK
Number of served transitions	...	2
Inputs	...	12
Outputs	...	8
Number of users	...	max. 12000 - Number of identifiers
Number of supported readers	<ul style="list-style-type: none"> • 4 pcs @ RS-485, • 4 pcs @ Wiegand 	...
Number of media per ID	...	8 - Proximity card, PIN code, fingerprint, etc.
Number of permissions per ID	...	100
Buffer memory	...	8 000 000 events buffer
MCT readers support	...	16 pcs
Readers connections	...	4 pcs - Wiegand / PRT
Number of login points	...	4
Number of access terminals	...	8
Number of access zones	...	4
Number of alarm zones	...	4
Input lines	<ul style="list-style-type: none"> • 4 pcs - Alarm inputs, • 2 pcs - Reed switch , • 2 pcs - Door/gate opening button, • 5 pcs - Tamper 	...
Number of automation nodes	...	4
Battery backup support	max. 7 Ah	12 V / 7 Ah
Output lines	<ul style="list-style-type: none"> • 2 pcs - Lock relay, • 4 pcs - Relay 	...
Communication	<ul style="list-style-type: none"> • RS-485, • Ethernet, • Wiegand (w26 / w34), • Open Supervised Device Protocol (OSDP) 	<ul style="list-style-type: none"> • Ethernet - RJ-45 socket • RS-485 interface • RACS 5 v2 (Roger)

Main features	<ul style="list-style-type: none"> • 100000 indexed users • History of 300000 events • Remote programming from PC • Metal housing 	<ul style="list-style-type: none"> • Integrated support in VISO EX software • Functions in the VISO EX system: - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system - unlimited - division of the system into partitions operated by independent operators - tool for integration with RACS5 (API) systems - integration with many systems (elevator systems, building applications, SMS, BMS, PSIM, VMS, Active Directory systems)
Power supply	100 ... 240 V AC	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC
Operation temp	-20 °C ... 65 °C	5 °C ... 40 °C
Permissible relative humidity	10 % ... 90 % (non-condensing)	10 % ... 95 % (non-condensing)
SAP Code	302913795	...
Weight	4.6 kg	0.14 kg
Dimensions	373 x 345 x 98 mm	175 x 72 x 30 mm
Manufacturer / Brand	Hikvision	ROGER
Guarantee	3 years	3 years