





	<a href="#">ACCESS CONTROLLER WITH TEMPERATURE MEASUREMENT DS-K1TA70MI-T - 1080p Hikvision</a>	<a href="#">ETHERNET + EPOE CONVERTER LR1002 DAHUA</a>	<a href="#">EXTERNAL CAMERA DISTRIBUTION POINT EXPERT-POE/OTD-82GSFP 8 PoE + 2 x SFP</a>	<a href="#">EXPANSION PLUG KW-8/5X80 KLIMAS</a>
				
	13566.78 DKK 13566.78 DKK	85.05 DKK 85.05 DKK	2429.24 DKK 2429.24 DKK	1.14 DKK 1.14 DKK
Scanning system	Progressive	...	...	...
Material	...	...	...	<ul style="list-style-type: none"> <li>Expansion plug, Polypropylene</li> <li>Screw, Steel galvanized</li> </ul>
In package	...	<b>2 pcs The price for package</b>	...	...
Drilling diameter	...	...	...	8 mm
Resolution	1920 x 1080 - 1080p	...	...	...
Expansion plug length	...	...	...	50 mm
Transmission ports	...	1 pcs BNC	...	...
Sensor	CMOS Uncooled VOx microbolometer	...	...	...
LAN ports	...	1 pcs RJ45	<ul style="list-style-type: none"> <li>8 x RJ45 10/100 Base-T ( 8 x PoE (802.3af/at) ),</li> <li>2 x SFP (Uplink) 1000 Base-X</li> </ul>	...
Matrix size	2.1 Mpx 120 x 160 px	...	...	...
Screw dimensions	...	...	...	Ø 5 x 80 mm, PZ-2
Management	...	...	—	...
Temperature measurement	✓	...	...	...
Temperature measurement range	30 °C ... 45 °C	...	...	...
Application	...	...	...	<ul style="list-style-type: none"> <li>Concrete</li> <li>Solid clay brick</li> <li>Solid sand-lime brick</li> </ul>
LED diodes	...	...	Power, Link/Act, PoE	...
Accuracy of temperature measurement	± 0.5 °C	...	...	...
Transmission range	...	max. 1000 m @ 10 Mbps max. 400 m @ 100 Mbps The range of data transfer and power supply is strongly dependent on the cable used and the power required to supply the receiver	...	...
Temperature measurement distance	0.3 ... 1.8 m	...	...	...
Cards support	13.56 MHz S50	...	...	...

Transmission speed	...	10 / 100 Mbps Full Duplex	<ul style="list-style-type: none"> <li>• 10 / 100 Mbps : 8 LAN &amp; PoE ports,</li> <li>• 1000 Mbps : 2 SFP (Uplink) ports</li> </ul>	...
Reading distance of prox-keys	~ 5 cm	...	...	...
Face recognition distance	0.3 m ... 1.8 m	...	...	...
Maximal output power	...	...	30 W @ PoE (802.3af/at) - 1 ... 8 ports	...
Maximal total power	...	...	115 W	...
MAC addresses table	...	...	16k	...
Memory	Memory of 6000 face templates Memory of 6000 RFID cards Non-volatile log buffer of the last 100 000 events	...	...	...
Standard	TCP/IP	...	...	...
IR illuminator	✓	...	...	...
LED illuminator	✓	...	...	...
Video output	—	...	...	...
Operation modes	...	...	<ul style="list-style-type: none"> <li>• E - EXTEND mode - ports 1, 2, 3, 4, 5, 6, 7, 8 support transmission up to 250 m</li> <li>• V - VLAN mode, 1 ... 8 ports are isolated from each other and separately work with the 9, 10 ports</li> <li>• P - PoE Auto-check mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected</li> </ul>	...
RS-485 interface	✓	...	...	...
Memory card slot	—	...	...	...
Number of line cables	...	...	2	...
Alarm inputs / outputs	2 / 1	...	...	...
Number of splice cassettes	...	...	1	...
Audio	Speaker built-in	...	...	...
Splice capacity	...	...	8	...
Connector type	...	...	SC / PC	...
Network interface	10/100/1000 Base-T (RJ-45)	...	...	...
Number of adapters	...	...	4	...
Network protocols	TCP/IP	...	...	...
Number of pigtails	...	...	4	...
WEB Server	—	...	...	...
ONVIF	—	...	...	...
Material	...	...	Metal	...

RS-485	✓	...	...	...
Default IP address	192.168.1.64	...	...	...
Default admin user / password	admin / - The administrator password should be set at the first start	...	...	...
PC client access ports	port 8000	...	...	...
Cable entries	...	...	3 pcs from the bottom Ø 39 mm	...
Main features	...	<ul style="list-style-type: none"> <li>• Plug &amp; Play</li> <li>• MDI/MDI-X auto detection feature - auto detecting the data transmission mode</li> <li>• Support for IP cameras and network devices</li> <li>• Easy installation - doesn't require any configuration of IP nor MAC address</li> <li>• 2 pcs included</li> </ul>	<ul style="list-style-type: none"> <li>• The door is closed with a lock</li> <li>• Fan cooler built-in</li> </ul>	...
Maximum pole diameter	...	...	350 mm	...
External dimensions	...	...	280 x 260 x 210	...
Certificates	...	...	CE, RoHS	...
Main features	<ul style="list-style-type: none"> <li>• Detection of people without a mask - access denied or voice alerts</li> <li>• Temperature measurement</li> <li>• 7 " capacitive touch screen - 1024 x 600 px</li> <li>• Mechanical tamper protection</li> <li>• Wiegand 34/26</li> <li>• AGC - Automatic Gain Control</li> <li>• Sharpness - sharper image outlines</li> <li>• Day/Night mode (color/b&amp;w/auto)</li> <li>• AI detection : A solution dedicated to measuring temperature. The camera is able to detect increased object temperature</li> </ul>	...	...	...
Power consumption	≤ 24 W	...	...	...
Housing	Compact - Metal	...	...	...
Color	Silver + Black	...	Gray	...
"Index of Protection"	—	...	IP55	...
Operation temp	0 °C ... 50 °C	...	...	...



Protections	...	Overvoltage	<ul style="list-style-type: none"> <li>• Protection against electrostatic discharge - Contact/Air (ESD/EMP) : 6 / 8 kV</li> <li>• Circuit Breaker : C10, protected lines L+N</li> <li>• Lightning protection : <ul style="list-style-type: none"> <li>- Maximal voltage : 385 V AC</li> <li>- Nominal stroke current : 20 kA (8/20μs)</li> <li>- Maximum stroke current : 40 kA (8/20μs)</li> </ul> </li> </ul>	...
Power supply	12 V DC / 2 A (power adapter not included)	ePoE	100 ... 240 V AC, 50 / 60 Hz - Screw terminals	...
Operation temp	...	...	-20 °C ... 65 °C	...
Weight	1.34 kg	0.030 kg	5.65 kg	...
Supported languages	Polish, English, French, Spanish, Portuguese, Russian, Italian	...	...	...
Manufacturer / Brand	Hikvision	DAHUA	...	KLIMAS
Dimensions	117 x 290 x 35 mm (without bracket)	- 56 x 27 x 21 mm - 7 cm (cable length)	280 x 260 x 205 mm	...
SAP Code	302917212	...	...	...
Guarantee	3 years	3 years	2 years	2 years