



|   |   |   |
|---|---|---|
|   | <a href="#">RFID PROXIMITY CARD ATLO-307*P50 13.56 MHz S50</a>                    | <a href="#">AHD, HD-CVI, HD-TVI, PAL VANDALPROOF CAMERA DS-2CE56D8T-ITMF(2.8MM) - 1080p Hikvision</a>                             |
|   |  |   |
|   | 23.14 USD<br>23.14 USD  | 82.59 USD<br>82.59 USD  |
| Standard  | ...   | AHD / HD-CVI / HD-TVI / CVBS  |
| In package  | <b>50 pcs The price for package</b>   | ...   |
| Sensor  | ...   | Progressive Scan CMOS   |
| Standard  | 13.56 MHz S50   | ...   |
| Matrix size                                       | ...   | 2.1 Mpx   |
| Compatibility                                     | ISO/IEC 14443A  | ...   |
| Possibility of programming the serial number (ID) | —   | ...   |
| Ability to write to internal memory               | 1 kB  | ...   |
| Serial Number overprint                           | —   | ...   |
| Main features                                     | Range : ~ 10 cm ,   | ...   |
| Resolution  | ...   | <ul style="list-style-type: none"> <li>• 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI</li> <li>• 960 x 576 - 960H @ PAL</li> </ul> |
| Range of IR illumination                          | ...   | 30 m  |
| IR illuminator power adjustment                   | ...   | Automatic   |
| Lens  | ...   | 2.8 mm  |
| View angle  | ...   | <ul style="list-style-type: none"> <li>• 104 ° (manufacturer data)</li> <li>• 101 ° (our tests result)</li> </ul>                 |
| IR illuminator support                            | ...   | ICR - Movable InfraRed filter   |
| S/N ratio   | ...   | > 62 dB   |
| Video output                                      | ...   | AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω  |

|                       |                  |  |
|-----------------------|------------------|--|
| Main features         | ...              | <ul style="list-style-type: none"> <li>• WDR <math>\geq</math> 130 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners</li> <li>• AGC - Automatic Gain Control</li> <li>• BLC - Back Light Compensation</li> <li>• ICR - Movable InfraRed filter</li> <li>• Auto White Balance</li> <li>• Mirror - Mirror image</li> <li>• Sharpness - sharper image outlines</li> </ul> |
| OSD menu              | ...              | OSD menu available via recorder  |
| Power supply          | ...              | 12 V DC / 280 mA   |
| Power consumption     | ...              | $\leq$ 3.4 W   |
| Housing               | ...              | Dome, Metal  |
| Color                 | ...              | White  |
| "Index of Protection" | ...              | IP67   |
| Vandal-proof          | ...              | —  |
| Operation temp        | ...              | -40 °C ... 60 °C   |
| Weight                | 0.005 kg         | 0.24 kg  |
| Dimensions            | 86 x 54 x 0.8 mm | 91 x 83 x 68 mm  |
| Manufacturer / Brand  | ATLO             | Hikvision  |
| SAP Code              | ...              | 300612680  |
| Guarantee             | 2 years          | 3 years  |