



	<a href="#">IP PTZ CAMERA INDOOR IPC-GK2CP-5C0WR Wi-Fi Ranger RC - 5 Mpx 3.6 mm IMOU</a>	<a href="#">IP SPEED DOME CAMERA OUTDOOR TC-H324S SPEC:25X/I/E/A/V/V3.0 - 1080p 4.8 ... 120 mm TIANDY</a>
		
	44.21 EUR 44.21 EUR	816.80 EUR 816.80 EUR
Standard	TCP/IP	IP
Matrix size	5 Mpx	...
Resolution	2688 x 1620 - 5 Mpx	1920 x 1080 - 1080p , 1280 x 720 720p
Sensor	1/3 " Progressive Scan CMOS	1/2.8 " Progressive Scan CMOS
Lens	3.6 mm	4.8 ... 120 mm
View angle	77 °	58 ° ... 2.8 °
Optical zoom	...	x 25
Digital zoom	...	x 16
Range of IR illumination	10 m	150 m
Video output	...	—
Preset rotation speed	...	• 240 °/s (horizontal) • 180 °/s (vertical)
Network protocols	TCP, DHCP	...
Rotation speed (manual control)	...	• 0.1 °/s ... 200 °/s (horizontal) • 0.1 °/s ... 120 °/s (vertical)
Horizontal rotation range	355 °	360 ° - continuous
Network interface	Wi-Fi - IEEE 802.11 b/g/n	...
Vertical rotation range	-10 ° ... 70 °	-16 ° ... 90 °
RS-485 interface	...	—
Number of presets	...	500
Horizontal scan	...	✓
Route settings	...	8
Image compression method	H.265 / H.264	S+265 / H.265 / H.264 / MJPEG
Alarm inputs / outputs	...	1 / 1
RTSP URL	—	...
Audio	• Microphone built-in, • Speakers built-in, • Bi-directional audio streaming support	• Audio input • Audio output
Main stream frame rate	25 fps @ 5 Mpx	25 fps @ 1080p

Interface	...	10/100 Base-T (RJ-45)
WEB Server	—	Built-in
Max. number of on-line users	...	32
ONVIF	✓	✓
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	Micro SD card support up to 512GB
Mobile phones support	Access by a cloud (P2P) • Android: Free application <a href="#">IMOU</a> • iOS (iPhone): Free application <a href="#">IMOU</a>	Port no.: 3000 or access by a cloud (P2P) • Android: Free application <a href="#">EasyLive Plus</a> • iOS (iPhone): Free application <a href="#">EasyLive Plus</a>
Access from PC	...	Port no.: 3000 or access by a cloud (P2P) - PC: Free application <a href="#">Easy7 Smart Client Express</a>
Default IP address	DHCP	DHCP or 192.168.1.2
Default admin user / password	admin / - The administrator password should be set at the first start	admin / - The administrator password should be set at the first start
Web browser access ports	—	80, 443, 3000, 3001, 3002, 23002
Mobile client access ports	—	3000, 3001
PC client access ports	—	3000, 3001
Port ONVIF	—	80
Intelligent image analysis	...	<ul style="list-style-type: none"> <li>• classification of people and vehicles</li> <li>• video tampering</li> <li>• abandoned/missing object</li> <li>• double crossing the line</li> <li>• crossing the line (tripwire)</li> <li>• intrusion</li> <li>• face detection</li> <li>• Intelligent Object Tracking</li> </ul>

Main features	<ul style="list-style-type: none"> <li>• Wi-Fi Module - IEEE 802.11 b/g/n, Range : 50 m (open area),</li> <li>• Motion Detection</li> <li>• People detection</li> <li>• Audio detection</li> <li>• area detection</li> <li>• Alarm notifications</li> <li>• Intelligent Object Tracking</li> <li>• Built-in alarm siren</li> <li>• Privacy Mode</li> <li>• Cooperation with IMOU recorders</li> <li>• Video calls</li> <li>• D-ZOOM - Digital Zoom</li> <li>• CALL button - Video calls</li> <li>• RESET button</li> </ul>	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 2D-DNR, 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Day/night mode</li> <li>• ICR - Movable InfraRed filter</li> <li>• Motion Detection</li> <li>• Image rotation and mirror</li> <li>• Adaptive adjusting of the IR illuminator power to the lens zoom and outdoor light conditions</li> </ul>
Protections	...	• Overvoltage protection : 6 kV
Power supply	5 V DC / 1 A (power adapter included)	• PoE (802.3at), • 12 V DC
Power consumption	< 5 W	≤ 22 W
Housing	...	Speed Dome, Aluminum
Color	...	White + Black
Operation temp	...	-30 °C ... 65 °C
"Index of Protection"	...	IP66
Mechanical protection class	...	—
Weight	0.17 kg	3.1 kg
Dimensions	Ø 80 x 110 mm (with stand)	Ø 161 x 276 mm (without bracket)
Supported languages	—	Polish, English, Albanian, Arabic, Korean, French, Hebrew, Spanish, Dutch, German, Portuguese, Russian, Thai, Turkish, Ukrainian, Vietnamese, Italian
Manufacturer / Brand	DAHUA / IMOU	TIANDY
Guarantee	2 years	3 years