



| | INDUSTRIAL POE SWITCH GTX-P1-5-41GSFP 4-PORT SFP | LASER LEVEL LM-570R-I UNI-T |
|----------------------------------|--|--|
| |  |  |
| | 90.63 EUR 90.63 EUR | 50.33 EUR 50.33 EUR |
| Laser color | ... | Red |
| Horizontal beam width (H) | ... | 110 ° |
| Vertical beam width (V) | ... | 110 ° |
| Light source power | ... | 10 mW |
| Laser wavelength | ... | 635 nm |
| Accuracy | ... | ± 3 mm / 10 m |
| Self-levelling range | ... | 3 ° ± 1 ° |
| Self-levelling time | ... | 3 s |
| Working distance | ... | 15 m ... 30 m |
| LAN ports | <ul style="list-style-type: none"> • 4 x RJ45 10/100 Base-T (2 x Hi-PoE + 2 x PoE (802.3af/at)), • 1 x RJ45 10/100/1000 Base-T - Uplink, • 1 x Port SFP 1000 Base-X - Uplink | ... |
| Backup time | ... | > 12 h |
| Possibility to mount on a tripod | ... | ✓ |
| Management | — | ... |
| Manufacturer / Brand | ... | UNI-T |
| LED diodes | Power, PoE, Link/Act | ... |
| Transmission speed | <ul style="list-style-type: none"> • 10 / 100 Mbps : 4 x Port LAN & PoE, • 10 / 100 / 1000 Mbps : 1 x Port RJ45 (Uplink), • 1000 Mbps : 1 x Port SFP (Uplink) | ... |
| Operation modes | <ul style="list-style-type: none"> • 250 m (Extend) - Range : 250 m @ 10 Mbps • VLAN - 1 ... 4 ports are isolated from each other and separately work with the 5, 6 ports • PD Alive • Port PoE Priority | ... |
| Maximal output power | <ul style="list-style-type: none"> • 60 W / port Hi-PoE - 1, 2 ports • 30 W / port PoE 802.3af/at - 3, 4 ports | ... |

| | | |
|----------------|---|-------------------------|
| Main features | <ul style="list-style-type: none"> • PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected • Ports 1 ... 4 support transmission priorities • The ability to connect two power adapters - redundant power supply • Industrial wide temperature design. • "Index of Protection" : IP40 • Devices for mounting on a DIN, TS-35 rail | ... |
| Certificates | CE, FCC, RoHS | ... |
| Protections | <ul style="list-style-type: none"> • Overvoltage : 6 kV • Contact/Air (ESD/EMP) : 6/8 kV | ... |
| Power supply | 48 ... 57 V DC - 2.1/5.5 mm socket or screw terminals (power adapter not included) | 2 x LR6 (AA) (included) |
| Operation temp | -40 °C ... 75 °C | ... |
| Weight | 0.5 kg | 0.211 kg |
| Dimensions | 145 x 103 x 45 mm | 76 x 74 x 65 mm |
| Guarantee | 2 years | 2 years |