



	<a href="#">ACCESS CONTROLLER MODULE MC16-PAC-ST-15 ROGER</a>	<a href="#">SWITCH POE GTX- CLM1-10-8G2G 8-PORT</a>
		
	578095.24 HUF 578095.24 HUF	57142.86 HUF 57142.86 HUF
Number of served transitions	15 (two-way)	...
Number of supported readers	60	...
Number of users	unlimited (purchase of the appropriate license required)	...
Number of media per ID	8 - Proximity card, PIN code, fingerprint, etc.	...
LAN ports	...	<ul style="list-style-type: none"> <li>• 8 x RJ45 ( 2 x Hi-PoE + 6 x PoE (802.3af/at) ),</li> <li>• 2 x RJ45 - Uplink</li> </ul>
Buffer memory	8 000 000 events buffer	...
Number of access zones	30	...
Management	...	✓
Number of alarm zones	30	...
Battery backup support	12 V / 7 Ah	...
Transmission speed	...	10 / 100 / 1000 Mbps : 2 x Port LAN - Uplink + 8 x Port LAN & PoE
Communication	<ul style="list-style-type: none"> <li>• Ethernet - RJ-45 socket</li> <li>• RACS 5 v2 (Roger)</li> <li>• RS-485 interface</li> </ul>	...
Operation modes	...	<ul style="list-style-type: none"> <li>• N - Normal - the device operates as normal PoE switch</li> <li>• V - VLAN (Port Isolation) - 1 ... 8 ports are isolated from each other and separately work with the 9, 10 ports</li> <li>• S - Extend - Range : 250 m @ 10 Mbps</li> </ul>
Default IP address	...	192.168.2.1
Default admin user / password	...	admin / admin
Maximal output power	...	<ul style="list-style-type: none"> <li>• 90 W / port Hi-PoE - 1, 2 ports</li> <li>• 30 W / port PoE - 3 ... 8 ports</li> </ul>
Maximal total power	...	120 W

Main features	<ul style="list-style-type: none"> <li>• Integrated support in VISO ST software</li> <li>• Functions in the VISO ST system: <ul style="list-style-type: none"> <li>- MSSQL database</li> <li>- work in distributed systems</li> <li>- multi-station work</li> <li>- monitoring of transitions with video preview</li> <li>- T&amp;A event reporting</li> <li>- maximum number of transitions in the system : 128</li> </ul> </li> </ul>	<ul style="list-style-type: none"> <li>• MDI/MDI-X auto detection feature - auto detecting the data transmission mode</li> <li>• Auto-learning and Auto-aging functions support for MAC addresses</li> <li>• QoS - mechanisms, which provide the high quality of transmission</li> <li>• MTBF (Mean Time Between Faults) : 50000 h</li> </ul>
Permissible relative humidity	10 % ... 95 % (non-condensing)	...
LED diodes	...	PWR, PoE, Link/Act
Manufacturer / Brand	ROGER	...
Certificates	...	CE, FCC, RoHS
Protections	...	Overvoltage $\pm$ 4 kV
Power supply	<ul style="list-style-type: none"> <li>• 17 ... 22 V AC</li> <li>• 10 ... 15 V DC</li> <li>• 22 ... 26 V DC</li> </ul>	48 ... 57 V DC, Power adapter included
Housing	...	Metal
Operation temp	5 °C ... 40 °C	-10 °C ... 55 °C
Weight	0.14 kg	0.45 kg
Dimensions	175 x 72 x 30 mm	185 x 95 x 27 mm
Guarantee	3 years	2 years