




	BATTERY 12.8V/12AH/LiFePO4-EP EUROPOWER	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR IDS-7232HOHI-M2/S(E) 32 CHANNELS Hikvision	COAXIAL CABLE TRISSET-113PE/500
			
	75.67 EUR 75.67 EUR	783.31 EUR 783.31 EUR	0.55 EUR 0.55 EUR
Battery capacity	12 Ah
Rated voltage	12.8 V
Battery charging current	max. 6 A
Battery type	LiFePO ₄ lithium-iron-phosphate battery
In section	500 m . Price for 1m when buying a whole roll
Standard	...	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP	...
Coaxial cable	TRISSET
Video inputs	...	32 pcs BNC	...
Battery lifetime	> 2000 cycles @ 80 % DoD
Inner conductor	Ø 1.13 mm Cu Wire
Connector	T2 (F2) type - FASTON 250
Dielectric	Ø 4.8 mm (physical foam)
Video outputs	...	1 pcs HDMI 1 pcs VGA 1 pcs CVBS - BNC socket	...
Audio inputs	...	1 pcs CINCH	...
Audio outputs	...	1 pcs CINCH	...
Shield	Al/PET/Al - 30 µm / 12 µm / 30 µm
Braid	81 % Al wire
Image compression method	...	H.265 / H.265+ / H.264 / H.264+	...
Outer coating	Ø 6.8 mm PE + gel
Coating color	Black
Resistance of the inner conductor for DC current	16.85 Ω/km
Capacity	52 pF/m
Dielectric resistance	2000 MΩ/km
Shortening wave coefficient	84 %
Impedance	75 Ω
Screening efficiency	≥ 90 dB @100-900 MHz
Minimal bend radius	35 mm
Main features	<ul style="list-style-type: none"> • low attenuation • perfect matched • high screening efficiency • Compliance with the class A standard • Compliance with the requirements of the MTBiGM regulation • Meets IEC68-2 Part 3 Accelerated Aging Standard
Operation temp	-30 °C ... 70 °C

Image records resolutions	...	<ul style="list-style-type: none"> • AHD : 4M-N - 1280 x 1440 , 1080p - 1920 x 1080 , 1080N - 960 x 1080 , 720p - 1280 x 720 , • HD-CVI : 4M-N - 1280 x 1440 , 1080p - 1920 x 1080 , 1080N - 960 x 1080 , 720p - 1280 x 720 , • HD-TVI : 4M-N - 1280 x 1440 , 1080p - 1920 x 1080 , 1080N - 960 x 1080 , 720p - 1280 x 720 , • CVBS : 960H - 960 x 576 , D1 - 704 x 576 , • IP : max. 6 Mpx - 3072 x 2048 	...
Recording speed adjustment	...	6 Mpx IP @ 1 ... 25 fps IP 4M-N @ 1 ... 15 fps 1080p @ 1 ... 15 fps 1080N @ 1 ... 25 fps 720p @ 1 ... 25 fps 960H @ 1 ... 25 fps for each channel	...
Operation modes	...	32 x HD-TVI / AHD / HD-CVI / PAL / IP + 8 x IP	...
Recording modes	...	Manual, Motion Detection, Schedule	...
Supported hard drives	...	2 x 10 TB SATA	...
External storage devices backup	...	Backup to USB drive (pendrive, external drive)	...
Searching and playback the records	...	Records searching: timeline or file list. Playback: forward, fast, slow. Playback max. 16 cameras in the same time	...
Network interface	...	1 x RJ-45 - 10/100/1000 Base-T	...
Bitrate	...	32 ... 6144 kbps	...
Network functions	...	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters	...
Network protocols	...	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP, HTTPS, ONVIF	...
Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) • Android: Free application Hik-Connect • Android: Free application Hik-Connect	...
Default IP address	...	DHCP or 192.168.1.64	...
Default admin user / password	...	admin / -	...
Web browser access ports	...	80	...
PC client access ports	...	554 RTSP, 8000	...
Mobile client access ports	...	8000	...
Port ONVIF	...	80	...
RTSP URL	...	<ul style="list-style-type: none"> • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream 	...
Alarm inputs / outputs	...	—	...

PTZ control	...	RS-485 PELCO-D/P Control compatible with coax HD-TVI Hikvision	...
Motion Detection	...	2.0	...
Main features	...	<ul style="list-style-type: none"> • DVR from the AcuSense series • Intelligent image analysis : intrusion, crossing the line (tripwire), Deep Learning technology • Filtering of false alarms based on the recognition of persons and vehicles • Motion detection with human/vehicle silhouette recognition 	...
Mouse support	...	✓	...
IR remote controller in the set	...	—	...
Power supply	...	12 V DC / 5 A (power adapter included)	...
Color	...	Black	...
Weight	1.3 kg	2.12 kg	40 kg/km
Dimensions	151 x 65 x 95 mm	380 x 330 x 52 mm	...
Supported languages	...	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Greek, Spanish, Dutch, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian	...
Manufacturer / Brand	EUROPOWER	Hikvision	...
SAP Code	...	300227850	...
Guarantee	5 years	3 years	5 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00