




	LITHIUM BATTERY BAT-AA-LITHIUM/E*P10 1.5 V L91 / FR6 (AA) ENERGIZER	UPS UPS07 800 VA Green Cell	EXTENDER HDMI PFM700-E DAHUA
			
	11180.77 HUF 11180.77 HUF	33630.77 HUF 33630.77 HUF	80000.00 HUF 80000.00 HUF
Power adapter type	...	Line-interactive	...
Nominal power	...	480 W	...
Apparent Power	...	800 VA	...
In package	10 pcs The price for package
Input voltage	...	162 V ... 290 V AC	...
Rated voltage	1.5 V
Type (size)	L91 / FR6 (AA)
Input frequency	...	50 / 60 Hz (auto detection)	...
Supported HDMI resolutions	1080p, 1080i, 720p, 576p, 576i, 480p, 480i
Maximal transmission range	60 m (max) @ 720p / 1080p - UTP cat. 5e, 6
Output voltage	...	<ul style="list-style-type: none"> • 230 V AC \pm 10 % (Approximated Sine Wave) • 5 V DC - USB Charger 	...
HDMI standard	1.3
Output frequency	...	50 / 60 Hz \pm 1 Hz	...
Transfer time	...	2 ... 6 ms (typical), max. 10 ms	...
Charging time (recover to 90% capacity)	...	6 ... 8 hours	...
Battery	...	1 pcs - 12V/9Ah	...
Estimated battery operation time	...	\leq 25 minutes - depending on the load	...
Power supply	5 V DC / 1000 mA (power adapter included) - TX side
Operation temp	-10 °C ... 55 °C
Permissible relative humidity	0 % ... 95 %
Number of outputs	...	<ul style="list-style-type: none"> • 6 pcs CEE 7/3 (Schuko), • 1 pcs USB-A - 5 V / 1 A 	...
Protections	...	<ul style="list-style-type: none"> • Short-circuit • Overvoltage • Overload • Overcharge • Discharge • Overheat • Ethernet filter - RJ-45 	...

Operation state indication	...	<ul style="list-style-type: none"> • LCD display: operation mode, battery charging level, in/out voltage level, Work load, Overload signaling, Failure signaling, Low battery level alarm, • Sound signaling 	...
Main features	<ul style="list-style-type: none"> • Very long operation time, • Operation temp : -40 °C ... 60 °C, • Weighs 1/3 less than standard alkaline batteries, • Holds power for up to 20 years of shelf life, • Leak-proof construction 	<ul style="list-style-type: none"> • Microprocessor control system • UPS auto diagnostic system • Automatic Voltage Regulator (AVR) • Auto restart while AC is recovering • "Cold Start" function • Battery charging at power-off mode • Fast intelligent battery recharge function • Remote management - GC UPS application (Display of operating parameters, schedule, e-mail personal messaging, local access) • USB interface • USB Charger, • USB A / USB B cable included + 2 x Power supply cable • The ergonomic shape - power outlets located on the top of the housing 	<ul style="list-style-type: none"> • IR receiver • An additional HDMI output in transmitter module • The distance switch (EQ) settings cause the initial signal correction • EDID support
Application	...	<ul style="list-style-type: none"> • Surveillance Systems • data storage centers • network, servers, workstations • Industrial Equipment 	...
Housing type	...	Desktop, Possibility to mount to the wall	...
Operation temp. / Relative humidity	...	0 °C ... 40 °C / 0 ... 90 %	...
Weight	0.014 kg	5.2 kg	0.134 kg
Dimensions	...	290 x 200 x 92 mm	79.5 x 68 x 16.5 mm
Manufacturer / Brand	ENERGIZER	Green Cell	DAHUA
Guarantee	2 years	2 years (12 months - battery)	3 years