




	<a href="#">IP VANDALPROOF CAMERA DS-2CD2183G2-I(2.8MM) ACUSENSE - 8.3 Mpx 4K UHD 2.8 mm Hikvision</a>	<a href="#">SERVER STANDING RACK CABINET R19-42U/800X1000/S SIGNAL</a>	<a href="#">CLEANING PASTE PEVALIN- PROFESSIONAL/250 TUBE 250 ml TESA</a>
			
	311.21 EUR 311.21 EUR	727.60 EUR 727.60 EUR	8.12 EUR 8.12 EUR
Standard	TCP/IP	...	...
Internal width	...	19 "	...
Package	...	...	Tube 250 ml
Internal height	...	42 U	...
Sensor	1/2.8 " Progressive Scan CMOS	...	...
External width	...	800 mm	...
Matrix size	8.3 Mpx	...	...
External height	...	2050 mm	...
External depth	...	1000 mm	...
Holes for fan coolers	...	105 x 105 mm (4 places)	...
Bearing capacity	...	1300 kg	...
Door	...	<ul style="list-style-type: none"> <li>• Front: perforated, steel</li> <li>• Side: metal, snap-in</li> <li>• Rear: perforated, steel</li> </ul>	...
Resolution	3840 x 2160 - 8.3 Mpx 4K UHD , 3200 x 1800 - 5.7 Mpx , 2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p	...	...
Lens	2.8 mm	...	...
View angle	<ul style="list-style-type: none"> <li>• 107 ° (manufacturer data)</li> <li>• 103 ° (our tests result)</li> </ul>	...	...
Range of IR illumination	30 m	...	...
RS-485 interface	—	...	...
Main features	...	<ul style="list-style-type: none"> <li>• Double doors</li> <li>• Removable side panels</li> <li>• Four rack rails for mounting devices (2x front, 2x rear)</li> <li>• Distance increments between rails of 1 cm</li> <li>• 2 vertical cable organizers</li> <li>• Cable entries are placed from the top and bottom</li> <li>• Possibility to mount the door as left or right</li> <li>• Lockable rear door and side panels</li> <li>• 12 keys included</li> <li>• Grounding connector</li> <li>• Possibility to mount 4 fans</li> <li>• Possibility to mount fan module</li> <li>• The cabinet moves on the lockable castors, stabilizing by twisting 4 leveler legs</li> </ul>	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...	...
Alarm inputs / outputs	—	...	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Audio	—	...	...
Memory card slot	Micro SD memory cards up to 512GB support (possible local recording)	...	...
Main stream frame rate	20 fps @ 8.3 Mpx 25 fps @ 5.7 Mpx	...	...
Network interface	10/100 Base-T (RJ-45)	...	...
Network protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP, IGMP, IEEE 802.1x, QoS, IPv4/IPv6, UDP, Bonjour, SSL / TLS, PPPoE, SNMP, WebSocket, WebSockets	...	...
WEB Server	Built-in	...	...
Max. number of on-line users	6	...	...
ONVIF	✓	...	...
Mobile phones support	Port no.: 8000 or access by a cloud (P2P) • Android: Free application <a href="#">Hik-Connect</a> • iOS: Free application <a href="#">Hik-Connect</a>	...	...
Default admin user / password	admin / -	...	...
Default IP address	192.168.1.64	...	...
Web browser access ports	80	...	...
PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	...	...
Mobile client access ports	8000	...	...
Port ONVIF	80	...	...
RTSP URL	• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization	...	...
Main features	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• RESET button</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Sharpness - sharper image outlines</li> <li>• Smart motion detection (with recognizing people and vehicles)</li> <li>• Configurable Privacy Zones</li> <li>• Vertical or horizontal image mirror</li> <li>• Day/night mode</li> <li>• ICR filter - IR illuminators support</li> <li>• AGC - Automatic Gain Control</li> <li>• Auto White Balance</li> <li>• Filtering of false alarms based on the recognition of persons and vehicles</li> <li>• Intelligent image analysis : crossing the line (tripwire), intrusion, face detection</li> </ul>	...	...
Power supply	• PoE (802.3af), • 12 V DC / 500 mA	...	...
Power consumption	• ≤ 7.5 W @ PoE (802.3af) • ≤ 6 W @ 12 V DC	...	...
Housing	Dome, Aluminum	...	...



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Vandal-proof	IK10	...	...
"Index of Protection"	IP67	...	...
Color	White	Black RAL9004	...
Operation temp	-30 °C ... 60 °C	...	...
Weight	0.52 kg	120 kg	...
Dimensions	Ø 111 x 85 mm	...	...
Supported languages	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Vietnamese, Italian	...	...
Manufacturer / Brand	Hikvision	SIGNAL	TESA
SAP Code	311315958	...	...
Guarantee	3 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00