

	IP CAMERA IPC2124LE-ADF28KMC-WL- BLACK ColorHunter - 4 Mpx 2.8 mm UNIVIEW	EXPANSION PLUG KW-10/6X60 KLIMAS	TOGGLE PLUG DUOTEC-10/SPH Fischer	EXTENDER RECEIVER HDMI-EX-150IR/RX-V4	ROUTER RG-EG210G-P 8 PoE REYEE
					
	216.42 EUR 216.42 EUR	0.17 EUR 0.17 EUR	1.13 EUR 1.13 EUR	79.57 EUR 79.57 EUR	236.76 EUR 236.76 EUR
Standard	TCP/IP
Device type	Receiver	...
Sensor	1/3 " Progressive Scan CMOS
HDMI standard	1.3	...
Matrix size	4 Mpx
HDCP	1.4	...
Material	...	<ul style="list-style-type: none"> Expansion plug, Polypropylene Screw, Steel galvanized 	<ul style="list-style-type: none"> Toggle Plug, Nylon Screw, Steel galvanized
Protocols	HDbitT	...
Drilling diameter	...	10 mm	10 mm
Expansion plug length	...	60 mm	40 mm
Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, 802.3z, IEEE 802.3af, IEEE 802.3at
Screw dimensions	...	Ø 6 x 60 mm, PZ-3	Ø 5 x 60 mm
Mounting panel thickness	9.5 ... 55 mm
LAN ports	<ul style="list-style-type: none"> 8 x LAN & PoE 10/100/1000 Mbps (RJ-45) 1 x LAN/WAN 10/100/1000 Mbps (RJ-45)
Cavity depth	min. 40 mm
Supported HDMI resolutions	1080p, 1080i, 720p, 576p, 576i, 480p, 480i	...
WAN interface	<ul style="list-style-type: none"> 1 x WAN 10/100/1000 Mbps (RJ-45)
Resolution	2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p
LED indicators	Status, Link/Act
Lens	2.8 mm
DDNS	✓
DHCP server	✓
Port USB	—
Application	...	<ul style="list-style-type: none"> Concrete Solid clay brick Solid sand-lime brick 	<ul style="list-style-type: none"> plasterboard Gypsum fibreboard OSB board MDF board Concrete Solid clay brick Solid sand-lime brick
View angle	<ul style="list-style-type: none"> 113 ° (manufacturer data) 97 ° (our tests result)
Firmware update	✓
Range of IR illumination	30 m
White light LED illuminator range	30 m
Maximal transmission range	<ul style="list-style-type: none"> 120 m @ 1080p - UTP cat. 6 100 m @ 1080p - UTP cat. 5e 80 m @ 1080p - UTP cat. 5 	...
S/N ratio	> 52 dB
RS-485 interface	—
Power supply PoE	Power output - LAN ports : PoE (802.3af/at) max. 70 W (total)

Memory card slot	Micro SD memory cards up to 128GB support (possible local recording)
Image compression method	Ultra 265 / H.265 / H.264 / MJPEG
Alarm inputs / outputs	—
Protections	<ul style="list-style-type: none"> • ACL • IP-MAC Binding • MAC addresses filtering • Support for dynamic ARP mapping and static table • NAT / NAPT • Port Mapping
Audio	<ul style="list-style-type: none"> • Microphone built-in • Speaker built-in • Audio detection • Bi-directional audio streaming support
Management interface	<ul style="list-style-type: none"> • Ruijie Cloud Central Management System • Configuration using the Ruijie Rejee application • Remote management • Web browser
Main stream frame rate	25 fps @ 4 Mpx
Network interface	10/100 Base-T (RJ-45)
Current consumption	3 W	...
Main features	<ul style="list-style-type: none"> • IR carrier frequency : 20 ... 60 kHz • Baudrate : 18 Mbps • Protections : lightning, Overvoltage, ESD 	<ul style="list-style-type: none"> • VPN networks: IPsec VPN, Open VPN, L2TP VPN, PPTP VPN, etc. • Static / dynamic routing • WAN : PPPoE, PPTP, L2TP • DHCP client/server support • Access Control List - ACL package filtering based on source and destination IP addresses • Rate limit • Load balance • NAT • Reboot schedule • View topology and network status • RESET button
Operation temp	0 °C ... 60 °C	0 °C ... 40 °C
Permissible relative humidity	10 % ... 90 % (non-condensing)
Network protocols	IPv4/IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, IEEE 802.1x, SNMP, SSL / TLS
WEB Server	Built-in
Max. number of on-line users	32
ONVIF	✓
Mobile phones support	<ul style="list-style-type: none"> Access by a cloud (P2P) • Android: Free application EZView • iOS (iPhone): Free application EZView 	<ul style="list-style-type: none"> Android: Free application Ruijie Rejee iOS (iPhone): Free application Ruijie Rejee
Default IP address	DHCP or 192.168.1.13
Default admin user / password	admin / 123456
Web browser access ports	80, 554
PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation
Mobile client access ports	80
Port ONVIF	80
RTSP URL	<ul style="list-style-type: none"> rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Mirror - Mirror image • Privacy zones - max. 4 • Motion detection with human/vehicle silhouette recognition • Sharpness - sharper image outlines • Intelligent image analysis : intrusion, crossing the line (tripwire) (human silhouette)
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 750 mA 	5 V DC / 1 A - (power adapter included)	100 ... 240 V AC, 50 / 60 Hz
Power consumption	≤ 9 W	≤ 80 W (at full load)
Housing	Compact, Metal + Plastic
Color	Black
"Index of Protection"	IP67
Vandal-proof	—
Operation temp	-30 °C ... 60 °C
Weight	0.42 kg	0.146 kg	0.53 kg
Dimensions	191 75 x 74 mm	97 x 94 x 24 mm	207 x 109 x 27 mm
Supported languages	Polish, English, Czech, Spanish, Dutch, French, German, Portuguese, Slovak, Hungarian, Italian
Manufacturer / Brand	UNIVIEW	KLIMAS	Fischer	...	RUIJIE / REYEE
Guarantee	3 years	2 years	2 years	2 years	2 years