



	IP CAMERA IPC-HFW3249E-AS-LED-0280B Full-Color - 1080p 2.8 mm DAHUA	IP CAMERA IPC-HFW1530S-0280B-S6 5 Mpx 2.8 mm DAHUA
		
	235.90 USD 235.90 USD	206.38 USD 206.38 USD
Standard	TCP/IP	TCP/IP
Sensor	1/2.8 " Progressive Scan CMOS	1/2.7 " Progressive Scan CMOS
Matrix size	2.1 Mpx	5 Mpx
White light LED illuminator range	30 m	...
Min. illumination	0.0015 Lux / F1.0 (color)	...
Resolution	1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p	2880 x 1620 - 5 Mpx , 2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2048 x 1536 - 3 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p
Lens	2.8 mm	2.8 mm
View angle	• 107 ° (manufacturer data) • 103 ° (our tests result)	• 106 ° (manufacturer data) • 102 (our tests result)
Range of IR illumination	...	30 m
RS-485 interface	—	—
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	—
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	H.265+ / H.265 / H.264 / H.264+ / MJPEG
Alarm inputs / outputs	1 / 1	—
Audio	• External microphone input • Audio output • Bi-directional audio streaming support	• Microphone built-in • Audio transmission via network • Audio detection
Main stream frame rate	25 fps @ 1080p	20 fps @ 5 Mpx 25 fps @ 4 Mpx
Network interface	10/100 Base-T (RJ-45)	10/100 Base-T (RJ-45)
Network protocols	IPv4/IPv6, HTTP, HTTPS, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, PPPoE, IEEE 802.1x, SNMP	IPv4/IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, SMTP, FTP, DHCP, DNS, DDNS, NTP, Multicast
WEB Server	Built-in	Built-in
Max. number of on-line users	20	6
ONVIF	20.06	20.06
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • ICR - Movable InfraRed filter • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Motion Detection • Configurable Privacy Zones • Mirror - Mirror image • SMD PLUS - searching for an object classified as: human, motor vehicle, non-motor vehicle • IVS analysis : crossing the line (tripwire) - classification of people and vehicles, intrusion, scene changing 	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Motion Detection • Privacy zones • Configurable Privacy Zones • Audio detection • Mirror - Mirror image
Default IP address	192.168.1.108	192.168.1.108
Default admin user / password	admin / - The administrator password should be set at the first start	admin / - The administrator password should be set at the first start
Power supply	• PoE (802.3af), • 12 V DC / 680 mA	• PoE (802.3af), • 12 V DC / 330 mA
Web browser access ports	80, 37777	80, 37777
PC client access ports	37777	37777
Mobile client access ports	37777	37777
Port ONVIF	80	80

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Power consumption	< 8.1 W	<ul style="list-style-type: none"> • ≤ 3.9 W @ 12 V DC • ≤ 4.5 W @ PoE (802.3af)
RTSP URL	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Housing	Compact - Metal	Compact - Metal
Color	White + Black	White
"Index of Protection"	IP67	IP67
Vandal-proof	—	...
Operation temp	-40 °C ... 60 °C	-40 °C ... 60 °C
Weight	0.58 kg	0.32 kg
Dimensions	193 x 71 x 66 mm	Ø 70 x 162 mm
Supported languages	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Russian, Romanian, Turkish, Ukrainian, Hungarian, Italian	English, Spanish, Russian
Manufacturer / Brand	DAHUA	DAHUA
Guarantee	3 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00