




	<a href="#">ACCESS CONTROLLER MODULE MC16-PAC-ST-3 ROGER</a>	<a href="#">ACCESS CONTROL PANEL ACCO-NT2 SATEL</a>	<a href="#">EXTENDER HDMI+USB- EX-100-4K</a>
			
	3170.86 DKK 3170.86 DKK	2822.98 DKK 2822.98 DKK	1533.61 DKK 1533.61 DKK
Number of served transitions	3 (two-way)	...	...
Number of supported readers	12	...	...
Inputs	...	<ul style="list-style-type: none"> <li>• 8 pcs - Mainboard inputs</li> <li>• max. 264</li> </ul>	...
Number of users	unlimited (purchase of the appropriate license required)	...	...
Number of media per ID	8 - Proximity card, PIN code, fingerprint, etc.	...	...
Outputs	...	<ul style="list-style-type: none"> <li>• 8 pcs - Mainboard inputs</li> <li>• max. 264</li> </ul>	...
Supported HDMI resolutions	...	...	480p, 576i, 576p, 720p 1080i, 1080p, 4K x 2K, 4K UHD
Buffer memory	8 000 000 events buffer	...	...
Number of access zones	6	...	...
Number of alarm zones	6	...	...
Events memory	...	<ul style="list-style-type: none"> <li>• Events saving to the micro SD card (included)</li> <li>• Recording up to 1 000 000 events from the control panel,</li> <li>• Max. 100 000 events read from each access control module</li> </ul>	...
Maximal transmission range	...	...	<ul style="list-style-type: none"> <li>• 70 m UTP cat. 6 @ 4K UHD,</li> <li>• 70 m UTP cat. 5, 5e @ 1080p</li> <li>• 50 m UTP cat. 5e @ 4K UHD (our tests result)</li> </ul>
Communication	<ul style="list-style-type: none"> <li>• Ethernet - RJ-45 socket</li> <li>• RACS 5 v2 (Roger)</li> <li>• RS-485 interface</li> </ul>	<ul style="list-style-type: none"> <li>• 2 x RS-485</li> <li>• Expander bus - up to 32 expander modules</li> </ul>	...
Main features	...	...	<ul style="list-style-type: none"> <li>• Extender also allows to extend an USB 2.0 port, eg. in order to control the recorder using the mouse</li> </ul>

Users + admins	...	<ul style="list-style-type: none"> <li>• 8000 + 1</li> <li>• Max. 65 000 users in the whole ACCO NET system</li> </ul>	...
Output load	...	<ul style="list-style-type: none"> <li>• OC : 50 mA / 12 V DC</li> <li>• +EX : 0.5 A / 12 V DC</li> <li>• AUX : 0.5 A / 12 V DC</li> </ul>	...
Main features	<ul style="list-style-type: none"> <li>• Integrated support in VISO ST software</li> <li>• Functions in the VISO ST system: <ul style="list-style-type: none"> <li>- MSSQL database</li> <li>- work in distributed systems</li> <li>- multi-station work</li> <li>- monitoring of transitions with video preview</li> <li>- T&amp;A event reporting</li> <li>- maximum number of transitions in the system : 128</li> </ul> </li> </ul>	<ul style="list-style-type: none"> <li>• Support for up to 255 access control modules</li> <li>• Ability to create up to 255 partitions in 1 control panel (up to 255 access control modules can be defined in one partition)</li> <li>• Ability to add up to 16 passageways (up to 16 partitions can be defined in each passageway)</li> <li>• Ability to block/unblock partition at a specified time, or as per access schedule,</li> <li>• Ability to assign 4 identifiers and a keyfob to a single user,</li> <li>• Ability to assign up to 4 proximity cards / DALLAS chips (iButtons) to a user,</li> <li>• Up to 256 access calendars, weekly schedules, daily schedules, time frames</li> <li>• Ability to control the control panel outputs by using keyfobs</li> <li>• Implementation of logic functions on inputs and outputs</li> <li>• Support for turnstiles</li> <li>• Electrical protection of all inputs and outputs as well as communication buses</li> </ul>	<ul style="list-style-type: none"> <li>• Very good image quality with no visible distortions caused by compression</li> <li>• No delays in video transmission</li> <li>• No delays in mouse control operations</li> <li>• Transition of the HDMI signal in the transmitter</li> <li>• S/PDIF output</li> </ul>
Power supply	<ul style="list-style-type: none"> <li>• 17 ... 22 V AC</li> <li>• 10 ... 15 V DC</li> <li>• 22 ... 26 V DC</li> </ul>	12 V DC / 140 mA (max)	<ul style="list-style-type: none"> <li>• Transmitter 5 V DC / 2 A (power adapter included)</li> <li>• Receiver 5 V / 2 A (power adapter included)</li> </ul>
Battery backup support	12 V / 7 Ah	—	...
Operation temp	5 °C ... 40 °C	-10 °C ... 55 °C	-20 °C ... 60 °C
Permissible relative humidity	10 % ... 95 % (non-condensing)	93 % (non-condensing)	0 % ... 90 % (non-condensing)
Weight	0.14 kg	0.096 kg	0.29 kg
Dimensions	175 x 72 x 30 mm	151 x 69 x 17 mm	150 x 107 x 28 mm - Transmitter or receiver dimensions
Manufacturer / Brand	ROGER	SATEL	...

Guarantee	3 years	2 years	2 years
-----------	---------	---------	---------



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00