

	REMOTE CONTROL FOR LED LIGHTING CONTROLLERS LED-CONTROL/RF 2.4 GHz, MONO, CCT, RGB, RGBW, RGB CCT (RGBWW) MiBOXER / Mi-Light	CYLINDRICAL MAGNETIC CONTACT B-2FLF-BR SATEL
		
	161.19 NOK 161.19 NOK	37.57 NOK 37.57 NOK
Detection	...	Opening the door or window
Maximum reed switched voltage	...	100 V
Application	Works with LED lighting : (RGB/RGBW/RGB CCT/CCT/MONO) 12-24V LED strips	...
Maximal switched current	...	500 mA
Number of channels	4	...
Make distance	...	15 mm
Wireless	2.4 GHz	...
Break distance	...	20 mm
Radio communication range (at open area)	30 m	...
Power supply	2 x 1.5V, type AAA/LR03 battery (not included)	...
Main features	Touch control keys	<ul style="list-style-type: none"> • Length of the cable : 45 cm • Mounting hole diameter for the sensor : 15 mm • Medium-sized body with a round flange
Housing	Plastic	...
Color	White	Brown
Operation temp	-20 °C ... 60 °C	...
Weight	0.07 kg (without battery)	0.006 kg
Dimensions	137 x 55 x 21 mm	Ø 18 x 6.3 mm (with flange)
Manufacturer / Brand	MiBOXER / Mi-Light	SATEL
Guarantee	2 years	2 years