



	<a href="#">EXTENDER HDMI-EX-120-V4</a>	<a href="#">SWITCH POE IP-8-20-H 8-PORT ATTE</a>
		
	1439.77 NOK 1439.77 NOK	3551.48 NOK 3551.48 NOK
Supported HDMI resolutions	480i, 576i, 480p, 576p, 720p, 1080p	...
LAN ports	...	<ul style="list-style-type: none"> <li>• 2 x RJ45 10/100/1000 Base-TX - Uplink</li> <li>• 8 x RJ45 10/100 Base-TX + PoE (802.3af/at) / Passive PoE</li> </ul>
Maximal transmission range	100 m UTP cat. 5e 120 m UTP cat. 6	...
Max. number of receivers working in the same time	237	...
Management	...	—
Protocols	HDBiT	...
Supported HDMI standard	1.3	...
LED diodes	...	Power, LAN
HDCP	1.4	...
Operation temp	0 °C ... 60 °C	...
Transmission speed	...	<ul style="list-style-type: none"> <li>• 10 / 100 Mbps : 8 LAN &amp; PoE ports</li> <li>• 10 / 100 / 1000 Mbps : 2 Port LAN</li> </ul>
Permissible relative humidity	10 % ... 90 % (non-condensing)	...
Maximal output power	...	<ul style="list-style-type: none"> <li>• 40 W @ Passive PoE - 1 ... 8 ports,</li> <li>• 30 W @ PoE (802.3at) - 1 ... 8 ports,</li> <li>• 15.4 W @ PoE (802.3af) - 1 ... 8 ports</li> </ul>
Maximal total power	...	96 W

Main features	...	<ul style="list-style-type: none"> <li>• Pin numbers for RJ-45 connector : 1/2, 3/6 - Wires to data transmission ; 4/5, 7/8 - Power supply</li> <li>• Possibility to connecting in cascade</li> <li>• Efficiency : 92 % @ 90 W</li> <li>• Built-in switching power supply : 48 V DC / 96 W</li> <li>• PSU thermal protection</li> <li>• Short-circuit protection</li> <li>• Overload protection</li> <li>• TAMPER switch indicating open the cover</li> <li>• The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 8 ports</li> <li>• Electronic fuse independently for each PoE channel</li> <li>• The modular design streamlines service tasks and enables quick and easy system expansion</li> <li>• The raster system of module assembly facilitates the expansion of the device by further modules</li> <li>• Main cable entries on the back of the enclosure</li> <li>• "Index of Protection" : IP20</li> </ul>
Power supply	5 V DC / 1 A (power adapter included)	180 ... 240 V AC - Built-in switching power supply
Weight	0.13 kg	4.33 kg
Dimensions	110 x 58 x 26 mm	400 x 450 x 140 mm
Manufacturer / Brand	...	ATTE
Guarantee	2 years	3 years