



	UPS AT-UPS2000RT-RACK 2000 VA EAST	WI-FI SMART PLUG ATLO- P2F-TUYA Wi-Fi, Tuya Smart
		
	1092.61 CAD 1092.61 CAD	15.06 CAD 15.06 CAD
Power adapter type	Online	...
Nominal power	1800 W	...
Rated voltage	...	220 ... 240 V AC
Maximal total load	...	3680 W
Apparent Power	2000 VA	...
Total maximal current	...	16 A
Number of outlets	...	2 pcs
Input voltage	230 V AC \pm 25 %	...
Socket type	...	CEE 7/3
Plug type	...	CEE 7/5
Input frequency	50 / 60 Hz (auto detection)	...
Grounding	...	✓
Output voltage	230 V AC \pm 5 % (Pure Sine Wave)	...
Output frequency	50 / 60 Hz \pm 1 %	...
Wireless	...	<ul style="list-style-type: none"> • Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n, • Bluetooth
Voltage adjustment	\pm 1 %	...
Mobile phones support	...	<ul style="list-style-type: none"> • The Tuya Smart free application on Android • The Tuya Smart free application on iOS
Frequency adjustment	—	...
Transfer time	0 ms	...
Charging time (recover to 90% capacity)	8 hours	...
Battery	4 x 12V/9Ah	...
Number of outputs	2 pcs CEE 7/3 (Schuko)	...
Management software	UPSmart (Windows 95/98/2000/XP/Vista/7/8/10, Linux)	...
Housing	...	Plastic
Color	...	White
Operation temp	...	-20 °C ... 50 °C
Permissible relative humidity	...	\leq 80 %

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Protections	<ul style="list-style-type: none"> • Fuse • Overvoltage • Overload protection • EPO (Emergency power off) switch • Ethernet filter 	...
Operation state indication	<ul style="list-style-type: none"> • LCD display: operation mode, battery charging level, in/out voltage level, overload indicator, • Sound signaling 	...
Main features	<ul style="list-style-type: none"> • Auto restart while AC is recovering • Automatic Voltage Regulator (AVR) • "Cold Start" function • Compatible with power generators • Remote management - UPSmart application included • Built-in EMI, RFI filter • Excellent microprocessor control guarantees high reliability • UPS auto diagnostic system • Battery charge and maintenance control • USB/RS-232 communication port 	<ul style="list-style-type: none"> • schedule, • timer, • remote access, • voice control • Energy measurement • ON/OFF button • STATUS indicator
Application	<ul style="list-style-type: none"> • Surveillance Systems • data storage centers • network, servers, workstations • Industrial Equipment 	...
Housing type	Rack/Tower 2-in-1 Design	...
Operation temp. / Relative humidity	0 °C ... 40 °C / 0 ~ 90 % (non-condensing)	...
Weight	22 kg	0.13 kg
Dimensions	440 x 88 x 658 mm ; RACK 19", 2U	97 x 50 x 83 mm
Manufacturer / Brand	EAST	ATLO
Guarantee	2 years	2 years