

	ACCESS CONTROLLER MC16-PAC-ST-3-KIT ROGER	VIDEO BALUN TR-1/SV OPTO-ISOLATOR	VIDEO SEPARATOR AHD, HD-CVI, HD-TVI, PAL PFM791 DAHUA	CABLE 2C-W/2C-G-5.0M 5 m
				
	638.94 CHF 638.94 CHF	32.28 CHF 32.28 CHF	17.35 CHF 17.35 CHF	1.26 CHF 1.26 CHF
Number of served transitions	3 (two-way)
Number of supported readers	12
Standard	...	• CVBS - PAL, NTSC
Standard	AHD, HD-CVI, HD-TVI, PAL	...
Number of users	unlimited (purchase of the appropriate license required)
Video transmission range	...	max. 400 m UTP cat. 5e
Cable	2 x CINCH Plug / 2 x CINCH Socket
Device type	...	Active	Passive	...
Number of inputs	1 - BNC socket	...
Length of the cable	5 m
Number of media per ID	8 - Proximity card, PIN code, fingerprint, etc.
Coaxial socket voltage range 75Ω (CVBS)	...	1 Vpp
Buffer memory	8 000 000 events buffer
Number of outputs	1 - BNC plug	...
Number of access zones	6
Number of channels	...	1
Input impedance	75 Ω	...
Number of alarm zones	6
Output impedance	75 Ω	...
Battery backup support	12 V / 20 Ah
Video bandwidth	...	0 ... 9 MHz (-3 dB)
Insertion loss	0.5 dB	...
CMRR (dB @ 5MHz)	...	50 dB
Coaxial socket impedance	...	75 Ω
Bandwidth	0 ... 65 MHz	...
Communication	• Ethernet - RJ-45 socket • RACS 5 v2 (Roger) • RS-485 interface
Symmetrical socket impedance	...	100 Ω
Opto-isolation between input and output	...	1000 V (peak)	800 V - peak	...
Opto-isolation between power and signal inputs / outputs	...	1000 V (peak)
Coaxial socket type	...	BNC Straight socket

Symmetrical socket type	...	Cable terminals
ESD protection	600 V (contact discharge) 8000 V (air-gap discharge)	...
Main features	<ul style="list-style-type: none"> • Metal housing • The MCX4D I/O expander included • Integrated support in VISO ST software • Functions in the VISO ST system: <ul style="list-style-type: none"> - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system : 128 	...	<ul style="list-style-type: none"> • Overvoltage protection : 4 kV 10/700 µs • Compliance with IEC61000-4-2, IEC61000-4-5 standards • MTBF (Mean Time Between Faults) > 20000 h • Length of the cables 2 x 13 cm 	• Very easy and quick assembly
Housing type	ABS	...
Power supply	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC 	12 V DC / 90 mA	—	...
Operation temp	5 °C ... 40 °C	-50 °C ... 55 °C	-20 °C ... 55 °C	...
Permissible relative humidity	10 % ... 95 % (non-condensing)	< 95 %	0 % ... 95 %	...
Weight	4.08 kg	0.095 kg	0.034 kg	0.110 kg
Dimensions	405 x 365 x 120 mm	117 x 30 x 62 mm	42 x 23 x 16 mm	...
Manufacturer / Brand	ROGER	DELTA	DAHUA	...
Guarantee	3 years	3 years	3 years	2 years