

	RELAY OR-PI-457/1/230AC ORNO	STEEL MAST VZ10050 1 m	SWITCH POE GTX-B1-10-82G 8-PORT
			
	33.29 AUD 33.29 AUD	28.98 AUD 28.98 AUD	115.73 AUD 115.73 AUD
Number of relay outputs	1
Height of the mast	...	1 m	...
Mast diameter	...	Ø 50 mm	...
Number of sections	...	1	...
Wall thickness	...	2 mm	...
Material	...	Steel	...
Protection	...	Hot-dip galvanized	...
Possibility to combine to each other	...	✓	...
LAN ports	<ul style="list-style-type: none"> • 8 x RJ45 (1 x Hi-PoE + 7 x PoE (802.3af/at)), • 2 x RJ45 - Uplink
Rated power consumption	≤ 1.5 W (max)
Management	—
Relay maximal load	16 A / 250 V AC (max) 16 A / 24 V DC (max)
Output	1 x NO/NC
LED diodes	Power, V - VLAN (Port Isolation), S - Extend, PoE, Link/Act, Speed
Manufacturer / Brand	ORNO
Transmission speed	<ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps : 2 x Port LAN - Uplink, • 10 / 100 Mbps : 8 x Port LAN & PoE
Operation modes	<ul style="list-style-type: none"> • N - Normal - the device operates as normal PoE switch • V - VLAN (Port Isolation) - 1 ... 8 ports are isolated from each other and separately work with the 9, 10 ports • S - Extend - Range : 250 m @ 10 Mbps
Maximal output power	<ul style="list-style-type: none"> • 60 W / port Hi-PoE - Port 1 • 30 W / port PoE - 2 ... 8 ports
Maximal total power	120 W
MAC addresses table	2k

Main features	<ul style="list-style-type: none"> • DIN, TS-35 rail mounting • LED indication 	...	<ul style="list-style-type: none"> • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Full Duplex: IEEE802.3x, Half Duplex: Back Pressure • Auto-learning and Auto-aging functions support for MAC addresses • PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected • MTBF (Mean Time Between Faults) : 50000 h
Certificates	CE, FCC Class B
Protections	Overvoltage ± 4 kV
Power supply	230 V - AC	...	100 ... 265 V AC
Operation temp	-20 °C ... 50 °C	...	-10 °C ... 45 °C
Weight	0.065 kg	2.05 kg	0.77 kg
Dimensions	97 x 17 x 65 mm	...	210 x 150 x 35 mm
Guarantee	2 years	4 years	2 years