








	<a href="#">UTP / COAXIAL TRANSMITTER EOC-110KIT 2 PCS SET</a>	<a href="#">SWITCH POE CS4010-8GT-110 8-PORT DAHUA</a>	<a href="#">FLUSH BOX PO-80F/EPN Elektro-Plast</a>	<a href="#">FLUSH BOX PK-60/K-G/EPN Elektro-Plast</a>	<a href="#">WIRELESS DOORBELL WDP-05A3 AC 230V EURA</a>	<a href="#">ACCESS POINT 4G+ LTE +ROUTER RUT260 2.4 GHz 300 Mbps Teltonika</a>
						
	60.01 USD 60.01 USD	292.76 USD 292.76 USD	1.07 USD 1.07 USD	0.78 USD 0.78 USD	19.24 USD 19.24 USD	184.80 USD 184.80 USD
Frequency range	...	...	...	...	...	2.4 GHz
Number of sections	...	...	1	1	...	...
Transmission range	200 m @ RG6	...	...	...	...	...
Antenna type	...	...	...	...	...	1 x Omnidirectional antenna Wi-Fi - 5 dBi (SMA connector) , 2 x Omnidirectional antenna 4G LTE - 4 dBi (SMA-RP connector)
Standards	...	...	...	...	...	IEEE 802.11 b/g/n, 4G+ Cat.6 LTE, 3G
Material	...	...	Plastic	Plastic	...	...
Color	...	...	Brick red + White	Brick red	...	...
Montage hole diameter	...	...	...	Ø 68 mm	...	...
Transmission speed	10 / 100 Mbps Half Duplex	• 10 / 100 / 1000 Mbps : 8 LAN & PoE ports, • 10 / 100 / 1000 : 2 Uplink ports	...	...	...	...
Listen to the available sounds	...	...	...	...		...
Signaling mode	...	...	...	...	Sound signaling	...
Baud rates	...	...	...	...	...	11n : 300 Mbps 11g : 54 Mbps 11b : 11 Mbps LTE : 300 / 42 Mbps (4G / 3G)
Number of ring-tones	...	...	...	...	16	...
Volume adjustment	...	...	...	...	—	...
Maximal output power	...	• 90 W / port Hi-PoE / PoE 802.3bt - Port 1 • 30 W / port PoE 802.3af/at - 2 ... 8 ports	...	...	...	...
Operation range	...	...	...	...	max. 50 m in open area	...
Maximal total power	...	110 W	...	...	...	...
Frequency band	...	...	...	...	433.92 MHz	...
MAC addresses table	...	8k	...	...	...	...
Management	...	✓	...	...	...	...
LAN ports	1 pcs RJ45 1 pcs BNC socket	• 8 x RJ45 10/100/1000 Base-T ( 1 x Hi-PoE (802.3bt) + 7 x PoE (802.3af/at) ), • 2 x RJ45 10/100/1000 Base-T - Uplink	...	...	...	• 1 x 10/100 Mbps - WAN • 1 x 10/100 Mbps - LAN
Operation modes	...	Extend On : 250 m, 10 Mbps @ UTP cat. 5e, 6	...	...	...	...
"Index of Protection"	...	...	—	—	IP44 - Doorbell button	...
LED diodes	...	Power, System, PoE, Link/Act	...	...	...	...
Transmitter power	...	...	...	...	...	≤ 17.51 dBm @ 2.4 GHz ≤ 23 dBm @ 4G LTE ≤ 24 dBm @ 3G WCDMA
LED indicators	...	...	...	...	...	Power, WAN, WLAN, LAN, LTE - 3G/4G, Signal indicator
Network type	...	...	...	...	...	4G, 3G
Certificates	...	CE	...	...	...	...
Housing	...	Desktop, Metal	...	...	...	...
LTE	...	...	...	...	...	✓
QSS	...	...	...	...	...	—
WDS	...	...	...	...	...	—

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

DHCP server	...	...	...	...	...	✓
Protections	...	<ul style="list-style-type: none"> <li>• Protection against lightning discharges (common/differential) : 4 / 2 kV</li> <li>• Protection against electrostatic discharge - Contact/Air (ESD/EMP) : 6 / 8 kV</li> </ul>	...	...	...	<ul style="list-style-type: none"> <li>• WPA3-EAP</li> <li>• WPA3-SAE</li> <li>• WPA2-Enterprise - PEAP</li> <li>• WPA2-PSK</li> <li>• AES-CCMP</li> <li>• WEP</li> <li>• TKIP</li> <li>• Auto Cipher modes</li> <li>• Client separation</li> <li>• SSID hiding</li> <li>• MAC addresses filtering</li> </ul>
Management interface	...	...	...	...	...	Web browser, Teltonika RMS application, SMS
Main features	<ul style="list-style-type: none"> <li>• Plug &amp; Play</li> <li>• Support for IP cameras and network devices</li> <li>• Full transparency for networks</li> </ul>	<ul style="list-style-type: none"> <li>• Switch is managed through the web and the cloud (DoLink Care application)</li> <li>• PoE power mode : The device supports 8-pin power supply - wires : 1-2(+), 3-6(-), 4-5(+), 7-8(-)</li> <li>• Intelligent management of Power Supply Unit power's output stage</li> <li>• protection against lightning discharges and voltage differences and strokes between devices</li> <li>• Watchdog PoE</li> <li>• Loop Protection</li> <li>• Compliance with the LLDP protocol</li> <li>• Spanning Tree STP/RSTP</li> <li>• Port Based VLAN : 32</li> <li>• Data Flow Control (802.3x)</li> <li>• DHCP client</li> <li>• RESET button</li> <li>• Possibility to mount to the wall</li> </ul>	<ul style="list-style-type: none"> <li>• Flush-mounted, for hollow walls</li> <li>• opening lid</li> <li>• 2 special screws with holders to fastening to the wall - included</li> </ul>	<ul style="list-style-type: none"> <li>• Flush-mounted, for hollow walls</li> <li>• 2 special screws with holders to fastening to the wall - included</li> </ul>	The number of connected doorbells and cooperated buttons can be increased as required	<ul style="list-style-type: none"> <li>• Support for IoT (Internet of Things) systems,</li> <li>• Ability to work as a Hotspot,</li> <li>• Support for VoIP technology,</li> <li>• SIM socket</li> <li>• DHCP Relay support</li> <li>• DHCP client list</li> <li>• Static / dynamic routing</li> <li>• VPN support</li> <li>• Default address : 192.168.1.1</li> <li>• Configuration using the Teltonika RMS application</li> <li>• WAN Connection Backup - thanks to the fully functional WAN / LAN port, you can use various types of backup connections, including cable, fiber and DSL modems</li> </ul>
Power supply	...	54 V DC / 2.22 A (power adapter included)	...	...	<ul style="list-style-type: none"> <li>• 230 V AC - Wireless doorbell,</li> <li>• Battery CR2032 3V (included) - Doorbell button</li> </ul>	<ul style="list-style-type: none"> <li>• 9 V DC / 1 A (power adapter included)</li> <li>• 9 ... 30 V DC</li> <li>• 9 ... 30 V DC - Passive PoE, Powering from LAN1</li> </ul>
Power consumption	...	max. 110 W	...	...	...	≤ 6.5 W
Operation temp	...	-10 °C ... 55 °C	...	...	...	-40 °C ... 75 °C
Permissible relative humidity	...	...	...	...	...	10 % ... 90 % (non-condensing)
Weight	0.055 kg (single element)	0.52 kg	0.036 kg	0.024 kg	<ul style="list-style-type: none"> <li>• 0.035 kg - Doorbell button</li> <li>• 0.09 kg - Wireless doorbell</li> </ul>	0.13 kg
Dimensions	72 x 25 x 25 mm (single element)	190 x 106 x 30 mm	<ul style="list-style-type: none"> <li>Ø 80 x 50 mm - Internal dimensions</li> <li>Ø 90 x 53 mm - External dimensions</li> </ul>	<ul style="list-style-type: none"> <li>Ø 60 x 47 mm - Internal dimensions</li> <li>Ø 67 x 48 mm - External dimensions</li> </ul>	<ul style="list-style-type: none"> <li>• 33 x 83 x 27 mm - Doorbell button</li> <li>• 55 x 110 x 68 mm - Wireless doorbell</li> </ul>	83 x 80 x 25 mm
Manufacturer / Brand	...	DAHUA	Elektro-Plast	Elektro-Plast	EURA	Teltonika
Guarantee	2 years	3 years	2 years	2 years	2 years	2 years