

	<a href="#">ROUTER RG-EG105G-V2 REYEE</a>	<a href="#">ROUTER RG-EG310GH-E REYEE</a>	<a href="#">LED FLOODLIGHT WITH MOTION SENSOR AD-NL-6252BLR4 ADVITI</a>	<a href="#">RFID PROXIMITY CARD ATLO-104N*P200</a>	<a href="#">HEX HEAD SCREW SS-M8X20/KL-8.8</a>
					
	139.72 EUR 139.72 EUR	310.41 EUR 310.41 EUR	12.31 EUR 12.31 EUR	59.79 EUR 59.79 EUR	0.14 EUR 0.14 EUR
Luminous flux	...	...	800 lm	...	...
Size	...	...	...	...	M8
Material	...	...	...	...	Steel galvanized
Strength class	...	...	...	...	8.8
In package	...	...	...	<b>200 pcs The price for package</b>	...
Light color	...	...	Neutral, 4000 K	...	...
Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, 802.3z	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, 802.3z	...	...	...
Standard	...	...	...	Unique EM 125kHz	...
Twilight switch	...	...	✓	...	...
Wrench size	...	...	...	...	13 mm
Compatibility	...	...	...	EM4100/4102	...
Thread length	...	...	...	...	20 mm
Possibility of programming the serial number (ID)	...	...	...	—	...
Nominal power	...	...	10 W	...	...
Ability to write to internal memory	...	...	...	—	...
LAN ports	• 3 x LAN 10/100/1000 Mbps (RJ-45) • 1 x LAN/WAN 10/100/1000 Mbps (RJ-45)	• 6 x LAN 10/100/1000 Mbps (RJ-45) • 3 x LAN/WAN 10/100/1000 Mbps (RJ-45)	...	...	...
Serial Number overprint	...	...	...	✓	...
Power factor	...	...	0.8	...	...
WAN interface	• 1 x WAN x 10/100/1000 Mbps (RJ-45)	• 1 x WAN x 10/100/1000 Mbps (RJ-45)	...	...	...
LED indicators	Status, Link/Act	Status, Link/Act	...	...	...
CRI	...	...	> 80	...	...
DDNS	✓	✓	...	...	...
DHCP server	✓	✓	...	...	...
Port USB	—	—	...	...	...
Firmware update	✓	✓	...	...	...
Power supply PoE	—	—	...	...	...
Protections	<ul style="list-style-type: none"> <li>• ACL</li> <li>• IP-MAC Binding</li> <li>• MAC addresses filtering</li> <li>• Support for dynamic ARP mapping and static table</li> <li>• NAT / NAPT</li> <li>• Port Mapping</li> </ul>	<ul style="list-style-type: none"> <li>• ACL</li> <li>• IP-MAC Binding</li> <li>• MAC addresses filtering</li> <li>• Support for dynamic ARP mapping and static table</li> <li>• NAT / NAPT</li> <li>• Port Mapping</li> <li>• Mechanisms to prevent the most common types of DoS (Denial-of-Service) attacks</li> </ul>	...	...	...
Management interface	<ul style="list-style-type: none"> <li>• Ruijie Cloud Central Management System</li> <li>• Configuration using the Ruijie Reeye application</li> <li>• Remote management</li> <li>• Web browser</li> </ul>	<ul style="list-style-type: none"> <li>• Ruijie Cloud Central Management System</li> <li>• Configuration using the Ruijie Reeye application</li> <li>• Remote management</li> <li>• Web browser</li> </ul>	...	...	...
Mobile phones support	Android: Free application <a href="#">Ruijie Reeye</a> iOS (iPhone): Free application <a href="#">Ruijie Reeye</a>	Android: Free application <a href="#">Ruijie Reeye</a> iOS (iPhone): Free application <a href="#">Ruijie Reeye</a>	...	...	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Housing	...	...	Aluminum	...	...
"Index of Protection"	...	...	IP44	...	...
Main features	<ul style="list-style-type: none"> <li>• VPN networks: IPsec VPN, Open VPN, L2TP VPN, PPTP VPN, etc.</li> <li>• Static / dynamic routing</li> <li>• WAN : PPPoE, PPTP, L2TP</li> <li>• DHCP client/server support</li> <li>• Access Control List - ACL package filtering based on source and destination IP addresses</li> <li>• Rate limit</li> <li>• Load balance</li> <li>• NAT</li> <li>• View topology and network status</li> <li>• RESET button</li> </ul>	<ul style="list-style-type: none"> <li>• VPN networks: IPsec VPN, Open VPN, L2TP VPN, PPTP VPN, etc.</li> <li>• Static / dynamic routing</li> <li>• WAN : PPPoE, PPTP, L2TP</li> <li>• DHCP client/server support</li> <li>• Access Control List - ACL package filtering based on source and destination IP addresses</li> <li>• Rate limit</li> <li>• Load balance</li> <li>• NAT</li> <li>• Reboot schedule</li> <li>• View topology and network status</li> <li>• RESET button</li> </ul>	<ul style="list-style-type: none"> <li>• LED SMD diodes</li> <li>• LED lifetime 30 000 h</li> <li>• Solid workmanship</li> <li>• PIR detector - Built-in, Range : 4 ... 8 m, Detection angle : 120 °</li> <li>• PIR detection sensitivity adjustment,</li> <li>• Sensitivity adjustment of the twilight sensor : 10 ... 2000 lx,</li> <li>• Lighting time adjustment : 10 ... 600 s,</li> <li>• IK rating : IK04</li> </ul>	<ul style="list-style-type: none"> <li>• Serial Number Format : 8H10D + WEG24A</li> <li>• Range : ~ 11 cm</li> <li>• The TK-4100 chip</li> </ul>	DIN 933 compliance
Power supply	12 V DC / 0.5 A (power adapter included)	100 ... 240 V AC, 50 / 60 Hz	230 V AC	...	...
Power consumption	max. 6 W	≤ 15 W	...	...	...
Operation temp	0 °C ... 40 °C	0 °C ... 40 °C	-20 °C ... 50 °C	...	...
Permissible relative humidity	10 % ... 90 % (non-condensing)	10 % ... 90 % (non-condensing)	...	...	...
Weight	0.4 kg	2.4 kg	0.22 kg	0.006 kg	0.012 kg
Dimensions	207 x 109 x 28 mm	440 x 207 x 44 mm	105 x 130 x 65 mm	86 x 54 x 1 mm	...
Manufacturer / Brand	RUIJIE / REYEE	RUIJIE / REYEE	ORNO / ADVITI	ATLO	...
Guarantee	2 years	2 years	3 years	2 years	2 years